



COMPO L SOFT 93050

9 15736 9040 B



AVAILABLE IN

BLACK 9 15736 9040 B

CHROMED 9 15736 9040 C

DARK CHROMED 9 15736 9040 DC

WHITE 9 15736 9040 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 135
RECESSED DEPTH (MM)	130
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.462
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 20,1W / CRI>90 / 3000K-1800K / 2264lm
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	50°
LED TECHNICS (LIGHT SOURCE)	2264lm // 20,1W // 112lm/W
LED TECHNICS (LUMINAIRE)	1474lm // 23,1W // 64lm/W

Requirements

LED POWER SUPPLY 600 mA - DC

Accessories

COMPO L HONEYCOMB SINGLE USE B
COMPO L LINEAR SPREAD LENS
COMPO L SPREAD LENS
COMPO L SOFTENING LENS
COMPO L GLASS SBL

For detailed installation instructions, please consult the manual : [9_15736_XXX0_HAND.pdf](#)

DELTALIGHT

COMPO L SOFT 93050

9 15736 9040 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required

FINISH YOUR SPECIFICATION

LED Power supply

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

15710 4300

LED POWER SUPPLY MULTIPOWER 30W DIM8 600mA

1

15710 4800

LED POWER SUPPLY MULTIPOWER 20W DIM1 600mA

1

15710 5500

LED POWER SUPPLY MULTIPOWER 20W DALI DT6 600mA

1

Dimtype: DALI

Mounting kits



15710 0030 B MOUNTING KIT COMPO L TRIM B

Cutout dimension (mm): 92

15710 0030 W MOUNTING KIT COMPO L TRIM W



15710 0060 MOUNTING KIT COMPO L TRIMLESS

Cutout dimension (mm): 92

DELTALIGHT

COMPO L SOFT 93050

9 15736 9040 B

Light altering devices

15710 2100 B

COMPO L HONEYCOMB SINGLE USE B

☐

15710 2110

COMPO L LINEAR SPREAD LENS

☐

Cutout dimension (mm): 42

15710 2120

COMPO L SPREAD LENS

☐

Cutout dimension (mm): 42

15710 2130

COMPO L SOFTENING LENS

☐

Cutout dimension (mm): 42

15710 2140

COMPO L GLASS SBL

☐

Cutout dimension (mm): 42

Notes: