
DELTALIGHT




# SPY 52 ON TW 96530

**REFERENCE** 19825 9040 B

AVAILABLE IN
**BLACK** 19825 9040 B
**FULL WHITE** 19825 9040 FW
**WHITE** 19825 9040 W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Ceiling Surface mounted |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.4 |
| **ADJUSTABILITY** | 0° to 90° swiveling, 355° rotatable |
| **INFORMATION** | REFLECTOR FL-30°<br>EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)<br>Optional REFLECTORS 20° & 45° available |

| Electrical info | |
|---|---|
| **CLASS** | III |
| **DIM TYPE** | depending on power supply |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, ENEC, LCA |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm |
| **TM-30 VALUES** | Rf: 89 / Rg: 100 |
| **SDCM** | SDCM2 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 30° |
| **LED TECHNICS (LIGHT SOURCE)** | 1087lm // 9W // 121lm/W |
| **LED TECHNICS (LUMINAIRE)** | 694lm // 10,4W // 67lm/W |

**Requirements**

SPY 52 TUBE
LED POWER SUPPLY 500mA-DC TW

**Options**

COVERSET R 90-100

**Accessories**

HONEYCOMB 42
SPREAD LENS 42
LINEAR SPREAD LENS 42
SOFTENING LENS 42
GLASS SBL 42

DELTALIGHT

# SPY 52 ON TW 96530

19825 9040 B

For detailed installation instructions, please consult the manual : **19825_XXX0_HAND.pdf**


## FINISH YOUR SPECIFICATION

### LED power supplies

# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

**# of Fixtures**

**Min current | Max current**





**21012 0355** LED POWER SUPPLY 500mA-DC 2CH TW DIM5 — 2

**Dimtype: DALI**

**Cutout dimension (mm): 85**


### Coversets




**204 00 90 ANO** COVERSET R 90 ANO

**204 00 90 B** COVERSET R 90 B

**204 00 90 W** COVERSET R 90 W




**204 00 100 ANO** COVERSET R 100 ANO

**204 00 100 B** COVERSET R 100 B


**204 00 100 W** COVERSET R 100 W

DELTALIGHT


# SPY 52 ON TW 96530

19825 9040 B


## Light altering devices




**19810 0010 B** HONEYCOMB 42 SINGLE USE B





**19810 0020** LINEAR SPREAD LENS 42





**19810 0030** SPREAD LENS 42




**19810 0040** SOFTENING LENS 42





**19810 0050** GLASS SBL 42




**19810 0060 B** HONEYCOMB 42 DOUBLE USE B

## Finish your product




**19810 0100 B** SPY 52 TUBE B

**19810 0100 FBR** SPY 52 TUBE FBR

**19810 0100 FG** SPY 52 TUBE FG

**19810 0100 GC** SPY 52 TUBE GC

# SPY 52 ON TW 96530


19825 9040 B

**19810 0100 W** SPY 52 TUBE W

## Replaceable reflector / lens




**19810 0180** SPY 52 REFLECTOR 20°




**19810 0190** SPY 52 REFLECTOR 45°




**19810 0240** SPY 52 REFLECTOR 30°

Notes: