



SOLI - FORM 60 DOWN-UP 93067 MDL

27136 9320 W-W



AVAILABLE IN

BLACK-BLACK 27136 9320 B-B

BLACK-FLEMISH GOLD 27136 9320 B-FG

WHITE-BLACK 27136 9320 W-B

WHITE-WHITE 27136 9320 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.24 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 7W / CRI>90 (R9: 50) / 3000K / 1068lm UP: LED cluster 7W / CRI>90 (R9: 50) / 3000K / 1068lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	DOWN: 1068lm // 7W // 152lm/W UP: 1068lm // 7W // 152lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 908lm // 8W // 113lm/W UP: 716lm // 8W // 89lm/W

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

SOLI - FORM 60 DOWN-UP 93067 MDL

27136 9320 W-W

For detailed installation instructions, please consult the manual : [27136_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

SMART 48

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

12

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

12


Dimtype: WDL = wireless dimmable

LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

6


Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

15

Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W


6

Dimtype: non-dimmable

Cutout dimension (mm): 40

SOLI - FORM 60 DOWN-UP 93067 MDL

27136 9320 W-W



21012 0240 LED POWER SUPPLY 48V-DC / 200W

Dimtype: non-dimmable

Cutout dimension (mm): 40

12 ☐

COMPATIBLE COMPOSABLES

SOLISCAPE profile	Available Colours
  27111 0020 SOLI - PROFILE 2m	
  27111 0030 SOLI - PROFILE 3m	

Notes: