



SL19 - SPY 27 92730 MDL

27022 9220 GC

AVAILABLE IN



BLACK 27022 9220 B

FLEMISH BRONZE 27022 9220 FBR

FLEMISH GOLD 27022 9220 FG

GOLD COLOURED 27022 9220 GC

WHITE 27022 9220 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCLLED POWER SUPPLY 48V-DC SPY 27 TUBE included (B for all versions W for FW version)
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	D
CERTIFICATES	CB, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	459lm // 6,7W // 69lm/W

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

Accessories

VISOR 27

For detailed installation instructions, please consult the manual : [27022_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

SMART 48

of Fixtures

i # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

28

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

28


Dimtype: WDL = wireless dimmable

LED power supplies

of Fixtures

i # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

15


Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

36

Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W

15


Dimtype: non-dimmable

Cutout dimension (mm): 40

DELTALIGHT

SL19 - SPY 27 92730 MDL

27022 9220 GC




21012 0240 LED POWER SUPPLY 48V-DC / 200W

30 ☐

Dimtype: non-dimmable

Cutout dimension (mm): 40

Light altering devices




24144 0040 B VISOR 27 B

☐


COMPATIBLE COMPOSABLES

SHIFTLINE 19 profile

Available Colours



27011 0050 SL19 - PROFILE 2m



27011 0060 SL19 - PROFILE 3m



Notes: