





SUPERNOVA FLAT 95 PRISMATIC
DOWN-UP 930 DIM5

20615 9305 B

AVAILABLE IN
BLACK 20615 9305 B
WHITE 20615 9305 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	12.7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC PRISMATIC INCL.DIMMABLE LED POWER SUPPLY 1860mA (DOWN) / 500mA (UP) 2 DALI ADDRESSES
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, LCA, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 1860mA: LED cluster 79,4W / CRI>90 (R9: 68) / 3000K / 11477lm UP @ 500mA: 2 x (LED cluster 11,1W / CRI>90 (R9: 50) / 3000K / 1487lm)
TM-30 VALUES	Rf: 89 / Rg: 97 Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L70 > 60000 L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN @ 1860mA: 11477lm // 79,4W // 144lm/W UP @ 500mA: 2974lm // 22,2W // 134lm/W
LED TECHNICS (LUMINAIRE)	DOWN @ 1860mA: 8585lm // 91,3W // 94lm/W UP @ 500mA: 2784lm // 25,5W // 109lm/W

Requirements
SUSPENSION SET 25 DIM 3m
CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m
CENTRAL SUSPENSION SUPERNOVA FLAT
Options
CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
WIRELESS CONTROL DIM5

DELTA LIGHT



SUPERNOVA FLAT 95 PRISMATIC DOWN-UP 930 DIM5

20615 9305 B


For detailed installation instructions, please consult the manual : [20615_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

Miscellaneous control equipment

	300 90 004 ED5 WIRELESS CONTROL DIM5	☐
	Dimtype: WDL = wireless dimmable	
	Cutout dimension (mm): 45	






Coversets

	204 00 62 ANO COVERSET R 62 ANO	☐
	204 00 62 B COVERSET R 62 B	☐

DELTALIGHT

SUPERNOVA FLAT 95 PRISMATIC DOWN-UP 930 DIM5

20615 9305 B

	<u>204 00 62 W</u>	COVERSET R 62 W	☐
	<u>204 00 90 ANO</u>	COVERSET R 90 ANO	☐
	<u>204 00 90 B</u>	COVERSET R 90 B	☐
	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐
	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐

DELTA

LIGHT

SUPERNOVA FLAT 95 PRISMATIC DOWN-UP 930 DIM5

20615 9305 B

204 90 90 W

COVERSET S 90 W

☐

Suspension parts




274 97 10 B

CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m B

☐


274 97 10 W

CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m W

☐

328 25 43 ED

SUSPENSION SET 25 DIM 3m

☐

328 26 23 B

CENTRAL SUSPENSION SUPERNOVA FLAT 3m B

☐

328 26 23 W

CENTRAL SUSPENSION SUPERNOVA FLAT 3m W

☐

Electric connection parts



15225 0360 B

CONNECTION ST B

Cutout dimension (mm): 43

☐

15225 0360 W

CONNECTION ST W

☐

Notes: