
DELTALIGHT




COMPO S WALLWASH TW 965

REFERENCE 9 15717 9000 C

AVAILABLE IN
CHROMED 9 15717 9000 C
WHITE 9 15717 9000 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 90
RECESSED DEPTH (MM)	85
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.128
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	G

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,4W / CRI>90 / 2700K-6500K / 522lm
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 56000
BEAMANGLE	NA
LED TECHNICS (LIGHT SOURCE)	522lm // 5,4W // 97lm/W
LED TECHNICS (LUMINAIRE)	198lm // 6,2W // 32lm/W

Requirements

LED POWER SUPPLY 150 mA - DC

For detailed installation instructions, please consult the manual : **9_15717_XXX0_HAND.pdf**

DELTALIGHT

COMPO S WALLWASH TW 965

9 15717 9000 C

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **System ceiling**	15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
 **Plasterboard**	15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
 **Wood**	15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required

FINISH YOUR SPECIFICATION

LED Power supply

of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

15710 5700 LED POWER SUPPLY MULTIPOWER 12W DALI DT8 150mA — 1 ☐

Mounting kits



15710 0010 B MOUNTING KIT COMPO S TRIM B ☐

Cutout dimension (mm): 55

15710 0010 W MOUNTING KIT COMPO S TRIM W ☐



15710 0040 MOUNTING KIT COMPO S TRIMLESS ☐

Cutout dimension (mm): 55

Notes: