



OML50 - INFORM DU HO 984mm 24LED 93063 DIM5

31433 9335 B

BESCHIKBAAR IN
ZWART 31433 9335 B



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	1.5
INFO	CLUSTER DOWN: 5326lm/m CLUSTER UP: 2663lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Elektrische info

ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	DALI
ENERGIE KLASSE	E
CERTIFICATES	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 36,3W / CRI>90 (R9: 50) / 3000K / 5242lm UP: LED cluster 18,1W / CRI>90 (R9: 50) / 3000K / 2621lm
TM-30 WAARDEN	Rf: 92 / Rg: 100
SMD	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNIEK (LICHTBRON)	DOWN: 5242lm // 36,3W // 145lm/W UP: 2621lm // 18,1W // 145lm/W

Opties

WIRELESS CONTROL DIM5

Notes: