



ENTERO RD-S TRIMLESS WALLWASH TW 965


28466 9000 GC

AVAILABLE IN

BLACK 28466 9000 B

GOLD COLOURED 28466 9000 GC

WHITE 28466 9000 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	95
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.14
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WALLWASH EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	884lm // 10W // 85lm/W

Requirements

MOUNTING KIT ENTERO ROUND S

MOUNTING KIT AIR 105

LED POWER SUPPLY 500mA-DC TW (Remote)

For detailed installation instructions, please consult the manual : [28466_XXX0_HAND.pdf](#)


DELTA LIGHT

ENTERO RD-S TRIMLESS WALLWASH TW 965

28466 9000 GC

CEILING COMPATIBILITY			
Ceiling Type	Mounting Kit		
	System ceiling	 28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
	Plasterboard	 28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
	Stucanet	 28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
	Concrete + plaster	 28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
	Lintel + plaster	 28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
	Hollow-core slab + plaster	 28400 0010 - MOUNTING KIT ENTERO RD-S O.F.A.	Required
	Stretched ceiling	 28400 0070 - MOUNTING KIT ENTERO RD-S CSC	Required
		 28400 0130 - MOUNTING KIT ENTERO RD-S WSC	Required
	Ventilation in plasterboard	 29810 0100 - MOUNTING KIT SIDE AIR ONLY 1	Required
		 29810 0110 - MOUNTING KIT SIDE AIR 105	Required
		 29810 0120 - MOUNTING KIT NO AIR 105	Required
	Ventilation in concrete + plaster	 29810 0120 - MOUNTING KIT NO AIR 105	Required
		 29810 0130 - MOUNTING KIT TOP AIR 105	Required
		 29810 0200 - MOUNTING KIT TOP AIR ONLY 1	Required

FINISH YOUR SPECIFICATION


LED power supplies		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
	21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5 Dimtype: DALI Cutout dimension (mm): 85	2

DELTALIGHT

ENTERO RD-S TRIMLESS WALLWASH TW 965

28466 9000 GC

Mounting kits




28400 0010 MOUNTING KIT ENTERO RD-S O.F.A.

☐

Cutout dimension (mm): 105

Mounting kits stretched ceiling




28400 0070 MOUNTING KIT ENTERO RD-S CSC

☐

28400 0130 MOUNTING KIT ENTERO RD-S WSC

☐

Mounting kits side air + light




29810 0110 MOUNTING KIT SIDE AIR 105

☐

Cutout dimension (mm): 168

Mounting kits top air + light




29810 0130 MOUNTING KIT TOP AIR 105

☐

Cutout dimension (mm): 135

Mounting kits side air only



29810 0100 MOUNTING KIT SIDE AIR ONLY 1

☐


Cutout dimension (mm): 168

DELTALIGHT

ENTERO RD-S TRIMLESS WALLWASH TW 965

28466 9000 GC

Mounting kits top air only




29810 0200 MOUNTING KIT TOP AIR ONLY 1



Cutout dimension (mm): 135

Mounting kits no air



29810 0120 MOUNTING KIT NO AIR 105



Cutout dimension (mm): 168

Notes: