


COMPO S WALLWASH 927

9 15715 9200 C



AVAILABLE IN

CHROME 9 15715 9200 C

BLANC 9 15715 9200 W



EXCLUSIVELY AVAILABLE IN INDIA



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 90
RECESSED DEPTH (MM)	85
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.124
ADJUSTABILITY	0° à 30° inclinable, 355° rotatif

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6,4W / CRI>90 / 2700K / 476lm
SDMC	SDCM2
RISKGROUP	RG1
BEAMANGLE	NA
LED TECHNICS (LIGHT SOURCE)	476lm // 6,4W // 115lm/W
LED TECHNICS (LUMINAIRE)	211lm // 7,4W // 29lm/W

Requirements

LED POWER SUPPLY 350 mA - DC

For detailed installation instructions, please consult the manual : [9_15715_XXX0_HAND.pdf](#)

COMPO S WALLWASH 927

9 15715 9200 C

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required

FINISH YOUR SPECIFICATION

alimentation led

of Fixtures

 web2print_power_supply_info_box		Min current Max current
15710 3300	LED POWER SUPPLY MULTIPOWER 15W NO DIM 350mA	1->2 ☐
15710 3800	LED POWER SUPPLY MULTIPOWER 10W DIM8 350mA	1 ☐
15710 4500	LED POWER SUPPLY MULTIPOWER 12W DIM1 350mA	1 ☐
15710 5300	LED POWER SUPPLY MULTIPOWER 12W DALI DT6 350mA	1 ☐
Dimtype: DALI		

kit de montage

	15710 0010 B MOUNTING KIT COMPO S TRIM B	☐
Cutout dimension (mm): 55		
	15710 0010 W MOUNTING KIT COMPO S TRIM W	☐
	15710 0040 MOUNTING KIT COMPO S TRIMLESS	☐
Cutout dimension (mm): 55		

DELTALIGHT

COMPO S WALLWASH 927

9 15715 9200 C

Notes: