
DELTALIGHT




D-LINER 30 INF LOC2 1114 93058 RD

REFERENCE 32084 9320 B-B

AVAILABLE IN
BLACK-BLACK 32084 9320 B-B
WHITE-WHITE 32084 9320 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	0
ADJUSTABILITY	non adjustable
INFORMATION	48 x REFLECTOR FL-58° EXCL.LED POWER SUPPLY 520mA-DC INCL.1 x CABLE 2 x 0,75mm² - 0,5m + WIELAND PLUG GST08i2 male green

Electrical info	
CLASS	III
ENERGY CLASS	C
CERTIFICATES	EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 17,3W / CRI>90 / 3000K / 3058lm
LED TECHNICS (LIGHT SOURCE)	3058lm // 17,3W // 177lm/W
LED TECHNICS (LUMINAIRE)	2419lm // 19,9W // 122lm/W

Requirements

LED POWER SUPPLY SET LOC PARALLEL

Options

CONNECTING CABLE LOC PARALLEL

For detailed installation instructions, please consult the manual : **32084_XXX0_HAND.pdf**

DELTALIGHT

D-LINER 30 INF LOC2 1114 93058 RD

32084 9320 B-B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 **Acoustic climate-control ceiling Hunter Douglas 30BD**	-


FINISH YOUR SPECIFICATION

Emergency units

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



32010 0195 EMERGENCY UNIT 1h LOC PARALLEL DIM5 — 1

Dimtype: DALI

Current supply



32010 1200 T CONNECTOR LOC PARALLEL



32010 1310 CONNECTING CABLE LOC PARALLEL 1m



32010 1320 CONNECTING CABLE LOC PARALLEL 2m



32010 1330 CONNECTING CABLE LOC PARALLEL 3m



32010 1340 CONNECTING CABLE LOC PARALLEL 4m

DELTALIGHT

D-LINER 30 INF LOC2 1114 93058 RD

32084 9320 B-B




32010 1350 CONNECTING CABLE LOC PARALLEL 5m ☐

LED power supplies

of Fixtures


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




32010 0105 LED POWER SUPPLY SET LOC PARALLEL 520mA / 35W DIM5 — 1 ☐

Dimtype: DALI




32010 0145 LED POWER SUPPLY SET LOC PARALLEL 1040mA / 35W DIM5 — 2->2 ☐

Dimtype: DALI



32010 0425 LED POWER SUPPLY SET LOC PARALLEL 1560mA / 100W DIM5 — 3->3 ☐

Dimtype: DALI



32010 0455 LED POWER SUPPLY SET LOC PARALLEL 2080mA / 100W DIM5 — 4->4 ☐

Dimtype: DALI

Notes: