





D-LINER 30 INF LOC2 1114 93058 RD

32084 9320 W-W

AVAILABLE IN
BLACK-BLACK 32084 9320 B-B
WHITE-WHITE 32084 9320 W-W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	0
ADJUSTABILITY	non adjustable
INFORMATION	48 x REFLECTOR FL-58° EXCL.LED POWER SUPPLY 520mA-DC INCL.1 x CABLE 2 x 0,75mm² - 0,5m + WIELAND PLUG GST08i2 male green
Electrical info	
CLASS	III
ENERGY CLASS	C
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 17,3W / CRI>90 / 3000K / 3058lm
LED TECHNICS (LIGHT SOURCE)	3058lm // 17,3W // 177lm/W
LED TECHNICS (LUMINAIRE)	2419lm // 19,9W // 122lm/W
Requirements	
LED POWER SUPPLY SET LOC PARALLEL	
Options	
CONNECTING CABLE LOC PARALLEL	

For detailed installation instructions, please consult the manual : [32084_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY





Ceiling Type	Mounting Kit
 Acoustic climate-control ceiling Hunter Douglas 30BD	-

FINISH YOUR SPECIFICATION

Emergency units		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
Dimtype: DALI	32010 0195 EMERGENCY UNIT 1h LOC PARALLEL DIM5	1
	32010 1200 T CONNECTOR LOC PARALLEL	
	32010 1310 CONNECTING CABLE LOC PARALLEL 1m	
	32010 1320 CONNECTING CABLE LOC PARALLEL 2m	
	32010 1330 CONNECTING CABLE LOC PARALLEL 3m	
	32010 1340 CONNECTING CABLE LOC PARALLEL 4m	
	32010 1350 CONNECTING CABLE LOC PARALLEL 5m	

D-LINER 30 INF LOC2 1114 93058 RD

32084 9320 W-W

LED power supplies		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
 32010 0105 LED POWER SUPPLY SET LOC PARALLEL 520mA / 35W DIM5 Dimtype: DALI	1	
 32010 0145 LED POWER SUPPLY SET LOC PARALLEL 1040mA / 35W DIM5 Dimtype: DALI	2->2	
 32010 0425 LED POWER SUPPLY SET LOC PARALLEL 1560mA / 100W DIM5 Dimtype: DALI	3->3	
 32010 0455 LED POWER SUPPLY SET LOC PARALLEL 2080mA / 100W DIM5 Dimtype: DALI	4->4	

Notes: