



COMPO L TW 96520

9 15737 9020 B



AVAILABLE IN

NOIR 9 15737 9020 B

CHROME 9 15737 9020 C

CHROME FONCÉ 9 15737 9020 DC

BLANC 9 15737 9020 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 135
RECESSED DEPTH (MM)	130
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.466
ADJUSTABILITY	0° à 30° inclinable, 355° rotatif

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 17,8W / CRI>90 (R9: 50) / 2700K-6500K / 2054lm
RVALUES	rf: 89 / Rg: 100
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	2054lm // 17,8W // 116lm/W
LED TECHNICS (LUMINAIRE)	1181lm // 20,5W // 58lm/W

Requirements

LED POWER SUPPLY 500 mA - DC

Accessories

COMPO L HONEYCOMB SINGLE USE B

COMPO L LINEAR SPREAD LENS

COMPO L SPREAD LENS

COMPO L SOFTENING LENS

COMPO L GLASS SBL


For detailed installation instructions, please consult the manual : [9_15737_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required

FINISH YOUR SPECIFICATION

alimentation led	# of Fixtures
 web2print_power_supply_info_box	Min current Max current
15710 6000 LED POWER SUPPLY MULTIPOWER 20W DALI DT8 500mA	1

kit de montage	
 15710 0030 B MOUNTING KIT COMPO L TRIM B	
Cutout dimension (mm): 92	
15710 0030 W MOUNTING KIT COMPO L TRIM W	
 15710 0060 MOUNTING KIT COMPO L TRIMLESS	
Cutout dimension (mm): 92	

modifier les dispositifs de lumière	
15710 2100 B COMPO L HONEYCOMB SINGLE USE B	
15710 2110 COMPO L LINEAR SPREAD LENS	
Cutout dimension (mm): 42	

DELTALIGHT

COMPO L TW 96520

9 15737 9020 B

<u>15710 2120</u>	COMPO L SPREAD LENS	☐
--------------------------	---------------------	--------------------------

Cutout dimension (mm): 42

<u>15710 2130</u>	COMPO L SOFTENING LENS	☐
--------------------------	------------------------	--------------------------

Cutout dimension (mm): 42

<u>15710 2140</u>	COMPO L GLASS SBL	☐
--------------------------	-------------------	--------------------------

Cutout dimension (mm): 42

Notes: