





SUPERLOOP VC 120 SBL 927

REFERENCE 321 512 92 B

AVAILABLE IN
BLACK 321 512 92 B
FLEMISH BRONZE 321 512 92 FBR
FLEMISH GOLD 321 512 92 FG
WHITE 321 512 92 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	3.8
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL EXCL.LED POWER SUPPLY 900-1200mA-DC INCL.2 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 36,4-50,3W / CRI>90 (R9: 59) / 2700K / 5022-6665lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	6665lm // 50,3W // 132lm/W
LED TECHNICS (LUMINAIRE)	4005lm // 57,8W // 69lm/W

Requirements

LED POWER SUPPLY 900 / 1200mA-DC DIM
 SUPERLOOP POWERBOX H 900mA
 SUPERLOOP POWERBOX H 1200mA

For detailed installation instructions, please consult the manual : [321_512_93_HAND.pdf](#)

DELTALIGHT

SUPERLOOP VC 120 SBL 927

321 512 92 B

FINISH YOUR SPECIFICATION


Power box

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




321 55 309 ED5 B SUPERLOOP POWERBOX H 900mA DIM5 B

1

Dimtype: DALI

321 55 309 ED5 W SUPERLOOP POWERBOX H 900mA DIM5 W

1




321 55 312 ED1 B SUPERLOOP POWERBOX H8 1200mA DIM1 B

1

Dimtype: 1-10V

321 55 312 ED1 W SUPERLOOP POWERBOX H8 1200mA DIM1 W

1




20548 0015 B SUPERLOOP POWERBOX H9 900mA DIM5 B

1

Dimtype: DALI

20548 0015 W SUPERLOOP POWERBOX H9 900mA DIM5 W

1



20548 0025 B SUPERLOOP POWERBOX H9 1200mA DIM5 B

1

Dimtype: DALI

20548 0025 W SUPERLOOP POWERBOX H9 1200mA DIM5 W

1

LED power supplies

of Fixtures






of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

DELTALIGHT

SUPERLOOP VC 120 SBL 927

321 512 92 B

	300 90 129 LED POWER SUPPLY 900mA-DC / 60W DIM5	1	☐
Dimtype: DALI			
Cutout dimension (mm): 84			
	300 90 130 LED POWER SUPPLY 1200mA-DC / 60W DIM5	1	☐
Dimtype: DALI			
Cutout dimension (mm): 95			
	300 90 132 LED POWER SUPPLY 1200mA-DC / 70W DIM1	1	☐
Dimtype: 1-10V			
Cutout dimension (mm): 80			

Notes: