




OBIN ON 93036 DIM8

30511 9338 BROB

AVAILABLE IN
BLACK 30511 9338 B
BRUSHED ALU 30511 9338 BRA
BRUSHED ANTHRACITE 30511 9338 BRAT
BRUSHED BROWN BRONZE 30511 9338 BRBB
BRUSHED GOLD 30511 9338 BRG
BRUSHED OLD BRONZE 30511 9338 BROB
CREAM 30511 9338 CR
WHITE 30511 9338 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 45° swiveling, 360° rotatable
INFORMATION	LENS FL-36° INCL.DIMMABLE POWER SUPPLY
Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,6W / CRI>90 (R9: 52) / 3000K / 1524lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	36°
LED TECHNICS (LIGHT SOURCE)	1524lm // 11,6W // 131lm/W
LED TECHNICS (LUMINAIRE)	1315lm // 13,3W // 99lm/W

Requirements	
SPY 90 TUBE	
Accessories	
HONEYCOMB 75	

For detailed installation instructions, please consult the manual : [30511_XXX8_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Light altering devices



19810 0110 B HONEYCOMB 75 SINGLE USE B

☐

Finish your product



19810 0170 B SPY 90 TUBE B

☐

19810 0170 CR SPY 90 TUBE CR

☐

19810 0170 DC SPY 90 TUBE DC

☐

19810 0170 FBR SPY 90 TUBE FBR

☐

19810 0170 FG SPY 90 TUBE FG

☐

19810 0170 GC SPY 90 TUBE GC

☐

19810 0170 PB SPY 90 TUBE PB

☐

19810 0170 W SPY 90 TUBE W

☐

Notes:

DELTALIGHT

OBIN ON 93036 DIM8

30511 9338 BROB