
DELTALIGHT




KIX II 93030

REFERENCE 13534 9320 N

AVAILABLE IN
ALU GREY 13534 9320 A
ANTHRACITE 13534 9320 N





View on website

General info	
LOCATION	outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	1
ADJUSTABILITY	0° to 90° swiveling
INFORMATION	REFLECTOR FL-30° INCL.LED POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	C

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	683lm // 6,7W // 102lm/W

Accessories

KAP KIX
HONEYCOMB KIX

For detailed installation instructions, please consult the manual : **13534_XXX0_HAND.pdf**


DELTALIGHT

KIX II 93030


13534 9320 N

FINISH YOUR SPECIFICATION

Light altering devices



232 10 00 N KAP KIX N ☐



232 10 03 N HONEYCOMB KIX N ☐

Notes: