



OML50 - LED ARRAY D HE 2624mm 940 DIM5

31024 9405



[Bekijk op website](#)



Algemene info

| | |
|-------------------------------|----------------------------------------------------------------------------------------------------|
| LOCATIE | binnen |
| STOF EN WATERDICHTHEID | IP20 |
| GEWICHT (KG) | 2,2 |
| INFO | CLUSTER DOWN: 2898lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT |

Elektrische info

| | |
|---------------------------|----------------------|
| ELEKTRISCH | 220-240V / 0 50-60Hz |
| KLASSE | I |
| VOEDING INBEGREPEN | YES |
| DIM TYPE | DALI |
| ENERGIE KLASSE | D |
| CERTIFICATES | EPD, RCM |

Info lichtbron

| | |
|---------------------------------|------------------------------------------------------|
| LIGHTSOURCE NAME | LED |
| LICHTBRON | LED cluster 44,5W / CRI>90 (R9: 50) / 4000K / 7603lm |
| TM-30 WAARDEN | Rf: 90 / Rg: 101 |
| SMDC | SDCM3 |
| RISK-GROEP | RG1 |
| LM80 | L80 > 60000 |
| LED TECHNIEK (LICHTBRON) | 7603lm // 44,5W // 171lm/W |

Opties

WIRELESS CONTROL DIM5

Notes: