





M26L - SPY 39 WALLWASH SOFT 930 DIM5

23436 9005 BRAT

AVAILABLE IN

- BLACK** 23436 9005 B
- BRUSHED ALU** 23436 9005 BRA
- BRUSHED ANTHRACITE** 23436 9005 BRAT
- BRUSHED COPPER** 23436 9005 BRCU
- BRUSHED GOLD** 23436 9005 BRG
- BRUSHED OLD BRONZE** 23436 9005 BROB
- FLEMISH BRONZE** 23436 9005 FBR
- FLEMISH GOLD** 23436 9005 FG
- GOLD COLOURED** 23436 9005 GC
- WHITE** 23436 9005 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 360° rotatable
INFORMATION	WALLWASH LENS EXCL.LED POWER SUPPLY 48V-DC
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	F
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	341lm // 6,9W // 49lm/W
Requirements	
LED POWER SUPPLY 48V-DC	

For detailed installation instructions, please consult the manual : [23436_XXX5_HAND.pdf](#)

DELTALIGHT

M26L - SPY 39 WALLWASH SOFT 930 DIM5

23436 9005 BRAT

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

8


Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

20

Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W

8

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W

17

Dimtype: non-dimmable

Cutout dimension (mm): 40

COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)

Available Colours



23358 0000 SLM26L - PROFILE



23358 0010 SLM26L - PROFILE 1m



23358 0020 SLM26L - PROFILE 2m



DELTALIGHT

M26L - SPY 39 WALLWASH SOFT 930 DIM5

23436 9005 BRAT



23358 0030 SLM26L - PROFILE 3m



Notes: