

ENVIRONMENTAL PRODUCT DECLARATION

IN ACCORDANCE WITH EN 15804+A2 & ISO 14025 / ISO 21930

30111 XXX5

NOCTA RD80 VWFL

Delta Light nv



EPD HUB, HUB-3051

Published on 14.03.2025, last updated on 14.03.2025, valid until 13.03.2030

GENERAL INFORMATION

MANUFACTURER

Manufacturer	Delta Light nv
Address	Muizelstraat 2, 8560 Wevelgem, Belgium
Contact details	Sustainability@deltalight.com
Website	www.deltalight.com

EPD STANDARDS, SCOPE AND VERIFICATION

Program operator	EPD Hub, hub@epdhub.com
Reference standard	EN 15804+A2:2019 and ISO 14025
PCR	EPD Hub Core PCR Version 1.1, 5 Dec 2023 EN 50693 for electronic and electrical products and systems
Sector	Electrical product
Category of EPD	Third party verified EPD
Scope of the EPD	Cradle to gate with options, A4-B7, and modules C1-C4, D
EPD author	Tim Blomme
EPD verification	Independent verification of this EPD and data, according to ISO 14025: ☐ Internal verification ☒ External verification
EPD verifier	Abderazak Guiz, an authorized verifier acting for EPD Hub Limited.

The manufacturer has the sole ownership, liability, and responsibility for the EPD. EPDs within the same product category but from different programs may not be comparable. EPDs of construction products may not be comparable if

they do not comply with EN 15804 and if they are not compared in a building context.

PRODUCT

Product name	NOCTA RD80 VWFL
Additional labels	-
Product reference	30111 XXX5
Place of production	Delta Light N.V., Muizelstraat 2, 8560 Belgium
Period for data	FY2022
Averaging in EPD	No averaging
Variation in GWP-fossil for A1-A3	-%

ENVIRONMENTAL DATA SUMMARY

Declared unit	1 unit of luminaire
Declared unit mass	1.164 kg
GWP-fossil, A1-A3 (kgCO ₂ e)	2,78E+01
GWP-total, A1-A3 (kgCO ₂ e)	2,76E+01
Secondary material, inputs (%)	8.47
Secondary material, outputs (%)	73.3
Total energy use, A1-A3 (kWh)	86.9
Net freshwater use, A1-A3 (m ³)	0.11

PRODUCT AND MANUFACTURER

ABOUT THE MANUFACTURER

Belgian and family-run since 1989, Delta Light provides premium lighting solutions for architecture. Quality products, designed for comfort and developed to last, that stand for simplicity and consistency but also show unexpected detail, from a visible screw to an ingenious touch. Because in everything Delta Light does, at project start or follow-up, we always seek to add a little extra care — and work with our partners, to guarantee we can bring their visions to completion.

PRODUCT DESCRIPTION

As a range of full IP65 wall fixtures, Nocta is the example that form and function can be merged into one. Build around 4 types of optics, Nocta is available in a cylindrical or cubical design, both with a down or down-up light emission. The cubical version also has a wider brother with double light beams, a way to add a more decorative touch onto the wall. All of them have some functional design elements in common that define Nocta.

Specifications about the representative product: architectural exterior or interior surface mounted wall lighting, IP65 classification, class I, power supply included with input 220-240V/50-60Hz. Luminaire power up to 7W with one LED COB. Diameter 80mm with length of body 145mm. Wall plate of dimensions 120x60mm. Materials used are aluminium for the LED housing and wall plate, glass that covers the LED, stainless steel for the fastening materials and polycarbonate for the back part and LED bracket Further information can be found at www.deltalight.com.

PRODUCT RAW MATERIAL MAIN COMPOSITION

Raw material category	Amount, mass %	Material origin
Metals	83	Asia
Minerals	3	EU
Fossil materials	2	Asia, EU
Bio-based materials	-	-

BIOGENIC CARBON CONTENT

Product's biogenic carbon content at the factory gate

Biogenic carbon content in product, kg C	0
Biogenic carbon content in packaging, kg C	0.06

FUNCTIONAL UNIT AND SERVICE LIFE

Declared unit	1 unit of luminaire
Mass per declared unit	1.164 kg
Functional unit	448 lumen during a reference lifetime of 55 000 hours
Reference service life	19 years when the luminaire is operated for 8 hours a day

SUBSTANCES, REACH - VERY HIGH CONCERN

The product does not contain any REACH SVHC substances in amounts greater than 0,1 % (1000 ppm).

PRODUCT LIFE-CYCLE

SYSTEM BOUNDARY

This EPD covers the life-cycle modules listed in the following table.

Product stage			Assembly stage		Use stage							End of life stage				Beyond the system boundaries		
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D		
x	x	x	x	x	MND	MND	MND	MND	MND	x	MND	x	x	x	x	x		
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction/ demolition	Transport	Waste processing	Disposal	Reuse	Recovery	Recycling

Modules not declared = MND. Modules not relevant = MNR

MANUFACTURING AND PACKAGING (A1-A3)

The environmental impacts considered for the product stage cover the manufacturing of raw materials used in the production as well as packaging materials and other ancillary materials. Also, fuels used by machines, and handling of waste formed in the production processes at the manufacturing facilities are included in this stage. The study also considers the material losses occurring during the manufacturing processes as well as losses during electricity transmission.

The product is made of metals, plastics and electronic components. The component manufacturing happens outside of Delta Light with subcontractors (aluminium production, moulding, pcb production,...) and are then transported to Delta Light N.V. where they are assembled together. The finished product is packaged in packaging cardboard before being sent to the installation site.

TRANSPORT AND INSTALLATION (A4-A5)

Transportation impacts occurred from final products delivery to construction site (A4) cover fuel direct exhaust emissions, environmental impacts of fuel production, as well as related infrastructure emissions.

Transportation distance is defined according to the PCR. Average distance of transportation from production plant to building site is assumed as average 1340km, 592km, 179km for respectively boat, road and air transport. Vehicle capacity utilization volume factor is assumed to be 100% which means full load. In reality, it may vary but as role of transportation emissions in total results is small, the variety in load is assumed to be negligible. Empty returns are not taken into account as it is assumed that return trip is used by the transportation company to serve the needs of other clients. Transportation does not cause losses as products are packaged properly. Also, volume capacity utilisation factor is assumed to be 100% for the nested packaged products. Transportation impacts that occur from delivery of the product cover direct exhaust emissions of fuel, environmental impacts of fuel production, as well as related infrastructure emissions. Environmental impacts from installation into the building include waste packaging materials (A5) and release of biogenic carbon dioxide from wood pallets and cardboard. The impacts of energy consumption and the used ancillary materials during installation are considered negligible.

PRODUCT USE AND MAINTENANCE (B1-B7)


During the use phase, the product consumes electricity from regional (EU, North America, Asia and rest of the world) electricity grid mix (B6). Impacts due to electricity production include direct emissions to air, transformation and transmission losses. The reference service life is based on the LM80 report of the LED which is 55 000 hours. When the luminaire is operated 8 hours a day, this will result in an RSL of approximately 19 years.

Air, soil, and water impacts during the use phase have not been studied.

PRODUCT END OF LIFE (C1-C4, D)

Consumption of energy and natural resources in demolition process is assumed to be negligible. It is assumed that the waste is collected separately and transported to the waste treatment center. Transportation distance to treatment is assumed as 50 km and the transportation method is assumed to be lorry (C2). According to EN 50693:2019, the sequence of treatment operations occurring to the product shall include de-pollution, fractions separation and preparation (dismantling, crushing, shredding, sorting), recycling, other material recovery, energy recovery and disposal. In this study, the default values from table G.4 of EN 50693 is used for treating materials in different waste treatment methods. Due to the material and energy recovery potential of parts in the lighting system, the end-of-life product is converted into recycled raw materials, while the energy recovered from incineration displaces electricity and heat production (D). The wooden pallet and other plastic packaging used during transportation is also incinerated for energy recovery and/or recycled. The benefits and loads of incineration and recycling are included in Module D.

MANUFACTURING PROCESS



All estimations and assumptions regarding the cut off criteria and the allocation are declared in the part “Cut-off Criteria except the estimations/assumptions below:

- Module A2, A4 & C2: Vehicle capacity utilization volume factor is assumed to be 1 which means full load. It may vary but as the role of transportation emission in total results is small, the variety in load is assumed to be negligible. Empty returns are not considered as it is assumed that return trip is used by transportation companies to serve the needs of other clients.
- Module A4: Transportation does not cause losses as products are packaged properly. Also, volume capacity utilisation factor is assumed to be 1 for the nested packaged products. Additionally, transportation distances are based on a sales volume-based weighted average and a lorry is the assumed vehicle type used.
- Module B4 & B6: The product is assumed to undergo replacement of selected components in intervals of time (19 years when the luminaire is operated for 8 hours a day) based on the lifespan of parts and components. This is to ensure that the product is fully functional throughout its lifetime.
- Module C2: Transportation distance to e-waste handling facility is estimated as 50 km and the transportation method is assumed as lorry.
- Module C3, C4, D: The product undergoes dismantling, and the parts are sorted into metals, plastics, paint and electronics. The waste treatment percentages based on EN 50693 are assumed to be applicable. Module C3 accounts for energy and resource inputs for sorting and treating these waste streams for recycling and incineration with energy recovery. Ash from recycling processes is negligible. The recycled end-of-life materials are assumed to serve as secondary raw materials in manufacturing, while incinerated materials displace the need for electricity and heat production.

LIFE-CYCLE ASSESSMENT

CUT-OFF CRITERIA

The study does not exclude any modules or processes which are stated mandatory in the reference standard and the applied PCR. The study does not exclude any hazardous materials or substances. The study includes all major raw material and energy consumption. All inputs and outputs of the unit processes, for which data is available for, are included in the calculation. There is no neglected unit process more than 1% of total mass or energy flows. The module specific total neglected input and output flows also do not exceed 5% of energy usage or mass.

ALLOCATION, ESTIMATES AND ASSUMPTIONS

Allocation is required if some material, energy, and waste data cannot be measured separately for the product under investigation. All allocations are done as per the reference standards and the applied PCR. In this study, allocation has been done in the following ways:

Data type	Allocation
Raw materials	No allocation
Packaging material	No allocation
Ancillary materials	Allocated by mass or volume
Manufacturing energy and waste	Allocated by mass or volume

AVERAGES AND VARIABILITY

Type of average	No averaging
Averaging method	Not applicable
Variation in GWP-fossil for A1-A3	-%

No averaging is used

LCA SOFTWARE AND BIBLIOGRAPHY

This EPD has been created using One Click LCA EPD Generator. The LCA and EPD have been prepared according to the reference standards and ISO 14040/14044. The EPD Generator uses Ecoinvent v3.8, Plastics Europe, Federal LCA Commons and One Click LCA databases as sources of environmental data.

ENVIRONMENTAL IMPACT DATA

CORE ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, PEF

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP – total ¹⁾	kg CO ₂ e	2,56E+01	3,00E-01	1,67E+00	2,76E+01	0,00E+00	2,37E-01	MND	MND	MND	MND	MND	2,82E+02	MND	0,00E+00	5,45E-03	1,94E-01	1,32E-02	-1,36E+01
GWP – fossil	kg CO ₂ e	2,56E+01	3,00E-01	1,90E+00	2,78E+01	0,00E+00	4,98E-03	MND	MND	MND	MND	MND	2,81E+02	MND	0,00E+00	5,44E-03	1,94E-01	1,32E-02	-1,36E+01
GWP – biogenic	kg CO ₂ e	0,00E+00	0,00E+00	-2,32E-01	-2,32E-01	0,00E+00	2,32E-01	MND	MND	MND	MND	MND	-1,39E-17	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	-7,46E-03
GWP – LULUC	kg CO ₂ e	1,61E-02	1,79E-04	2,12E-03	1,84E-02	0,00E+00	3,03E-06	MND	MND	MND	MND	MND	5,90E-01	MND	0,00E+00	2,01E-06	1,06E-04	1,25E-05	-2,26E-03
Ozone depletion pot.	kg CFC ₋₁₁ e	8,89E-07	6,15E-08	1,55E-07	1,11E-06	0,00E+00	3,53E-10	MND	MND	MND	MND	MND	9,49E-06	MND	0,00E+00	1,25E-09	4,57E-09	1,30E-09	-3,88E-07
Acidification potential	mol H ⁺ e	2,56E-01	7,96E-03	5,91E-03	2,70E-01	0,00E+00	2,18E-05	MND	MND	MND	MND	MND	1,43E+00	MND	0,00E+00	2,30E-05	6,19E-04	7,55E-05	-1,34E-01
EP-freshwater ²⁾	kg Pe	2,27E-03	1,02E-06	9,96E-05	2,37E-03	0,00E+00	1,27E-07	MND	MND	MND	MND	MND	1,47E-02	MND	0,00E+00	4,46E-08	3,51E-06	3,63E-07	-8,73E-04
EP-marine	kg Ne	2,92E-02	1,99E-03	1,23E-03	3,25E-02	0,00E+00	3,78E-05	MND	MND	MND	MND	MND	2,41E-01	MND	0,00E+00	6,85E-06	8,40E-05	1,93E-05	-1,57E-02
EP-terrestrial	mol Ne	3,29E-01	2,21E-02	1,05E-02	3,61E-01	0,00E+00	6,27E-05	MND	MND	MND	MND	MND	2,69E+00	MND	0,00E+00	7,56E-05	9,86E-04	2,04E-04	-1,74E-01
POCP (“smog”) ³⁾	kg NMVOCe	9,63E-02	5,74E-03	3,13E-03	1,05E-01	0,00E+00	2,32E-05	MND	MND	MND	MND	MND	7,26E-01	MND	0,00E+00	2,42E-05	2,80E-04	6,10E-05	-5,10E-02
ADP-minerals & metals ⁴⁾	kg Sbe	1,00E-03	3,69E-07	8,42E-06	1,01E-03	0,00E+00	5,03E-08	MND	MND	MND	MND	MND	1,32E-03	MND	0,00E+00	1,28E-08	6,60E-06	2,67E-08	-7,61E-05
ADP-fossil resources	MJ	2,61E+02	3,86E+00	3,18E+01	2,96E+02	0,00E+00	4,22E-02	MND	MND	MND	MND	MND	3,66E+03	MND	0,00E+00	8,18E-02	9,02E-01	1,62E-01	-1,33E+02
Water use ⁵⁾	m ³ e depr.	9,18E+01	1,07E-02	1,19E+00	9,30E+01	0,00E+00	1,78E-03	MND	MND	MND	MND	MND	7,70E+01	MND	0,00E+00	3,66E-04	2,29E-02	2,05E-03	-1,37E+00

1) GWP = Global Warming Potential; 2) EP = Eutrophication potential. Required characterisation method and data are in kg P-eq. Multiply by 3,07 to get PO4e; 3) POCP = Photochemical ozone formation; 4) ADP = Abiotic depletion potential; 5) EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and Ionizing radiation, human health. The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

ADDITIONAL (OPTIONAL) ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, PEF

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Particulate matter	Incidence	1,58E-06	9,32E-09	3,43E-08	1,62E-06	0,00E+00	3,15E-10	MND	MND	MND	MND	MND	1,08E-05	MND	0,00E+00	6,27E-10	1,04E-08	1,15E-09	-7,60E-07
Ionizing radiation ⁶⁾	kBq 11235e	1,51E+00	1,78E-02	3,30E-01	1,86E+00	0,00E+00	4,21E-04	MND	MND	MND	MND	MND	4,10E+01	MND	0,00E+00	3,89E-04	5,46E-03	9,44E-04	-7,52E-01
Ecotoxicity (freshwater)	CTUe	9,31E+02	2,43E+00	2,67E+01	9,60E+02	0,00E+00	2,65E-01	MND	MND	MND	MND	MND	5,55E+03	MND	0,00E+00	7,35E-02	4,64E+00	1,74E+02	-2,74E+02
Human toxicity, cancer	CTUh	4,03E-08	1,50E-10	5,55E-10	4,10E-08	0,00E+00	9,18E-12	MND	MND	MND	MND	MND	8,48E-08	MND	0,00E+00	1,81E-12	1,07E-10	1,04E-11	3,54E-09
Human tox. non-cancer	CTUh	1,01E-06	2,01E-09	1,64E-08	1,03E-06	0,00E+00	1,91E-10	MND	MND	MND	MND	MND	3,13E-06	MND	0,00E+00	7,28E-11	4,55E-09	2,76E-10	-3,15E-07
SQP ⁷⁾	-	6,66E+01	7,23E-01	8,20E+00	7,55E+01	0,00E+00	3,88E-02	MND	MND	MND	MND	MND	5,93E+02	MND	0,00E+00	9,42E-02	9,15E-01	2,18E-01	-5,09E+01

6) EN 15804+A2 disclaimer for Ionizing radiation, human health. This impact category deals mainly with the eventual impact of low-dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator; 7) SQP = Land use related impacts/soil quality.

USE OF NATURAL RESOURCES

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Renew. PER as energy ⁸⁾	MJ	1,07E+01	2,48E-02	6,17E+00	1,69E+01	0,00E+00	3,32E-03	MND	MND	MND	MND	MND	4,75E+02	MND	0,00E+00	9,21E-04	1,24E-01	1,02E-02	-4,50E+00
Renew. PER as material	MJ	0,00E+00	0,00E+00	2,03E+00	2,03E+00	0,00E+00	-2,03E+00	MND	MND	MND	MND	MND	0,00E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	-1,83E+00
Total use of renew. PER	MJ	1,07E+01	2,48E-02	8,20E+00	1,89E+01	0,00E+00	-2,02E+00	MND	MND	MND	MND	MND	4,75E+02	MND	0,00E+00	9,21E-04	1,24E-01	1,02E-02	-6,33E+00
Non-re. PER as energy	MJ	2,60E+02	3,86E+00	3,18E+01	2,96E+02	0,00E+00	4,21E-02	MND	MND	MND	MND	MND	3,66E+03	MND	0,00E+00	8,18E-02	9,02E-01	1,62E-01	-1,33E+02
Non-re. PER as material	MJ	3,01E-01	0,00E+00	1,65E-02	3,18E-01	0,00E+00	-1,65E-02	MND	MND	MND	MND	MND	0,00E+00	MND	0,00E+00	0,00E+00	-1,51E-01	-1,51E-01	-8,41E-03
Total use of non-re. PER	MJ	2,61E+02	3,86E+00	3,18E+01	2,96E+02	0,00E+00	2,57E-02	MND	MND	MND	MND	MND	3,66E+03	MND	0,00E+00	8,18E-02	7,51E-01	1,13E-02	-1,33E+02
Secondary materials	kg	9,86E-02	1,43E-03	1,61E-01	2,61E-01	0,00E+00	7,75E-05	MND	MND	MND	MND	MND	3,37E-01	MND	0,00E+00	2,27E-05	7,25E-04	4,06E-05	7,24E-01
Renew. secondary fuels	MJ	2,29E-03	4,60E-06	1,13E-02	1,36E-02	0,00E+00	3,90E-07	MND	MND	MND	MND	MND	2,34E-03	MND	0,00E+00	2,29E-07	2,78E-05	2,51E-06	-4,30E-04
Non-ren. secondary fuels	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	MND	MND	MND	MND	0,00E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Use of net fresh water	m ³	9,38E-02	2,41E-04	1,41E-02	1,08E-01	0,00E+00	2,88E-05	MND	MND	MND	MND	MND	2,15E+00	MND	0,00E+00	1,06E-05	6,15E-04	1,28E-04	-2,71E-02

8) PER = Primary energy resources.

END OF LIFE – WASTE

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Hazardous waste	kg	4,35E+00	4,50E-03	6,69E-02	4,42E+00	0,00E+00	8,69E-04	MND	MND	MND	MND	MND	2,36E+01	MND	0,00E+00	1,08E-04	1,53E-02	0,00E+00	-2,04E+00
Non-hazardous waste	kg	7,22E+01	4,01E-02	4,05E+00	7,63E+01	0,00E+00	9,26E-03	MND	MND	MND	MND	MND	6,34E+02	MND	0,00E+00	1,78E-03	3,33E-01	3,16E-01	-3,81E+01
Radioactive waste	kg	5,86E-04	2,74E-05	9,56E-05	7,09E-04	0,00E+00	2,15E-07	MND	MND	MND	MND	MND	1,13E-02	MND	0,00E+00	5,47E-07	2,09E-06	0,00E+00	-2,86E-04

END OF LIFE – OUTPUT FLOWS

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Components for re-use	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	MND	MND	MND	MND	0,00E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Materials for recycling	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	1,30E-01	MND	MND	MND	MND	MND	0,00E+00	MND	0,00E+00	0,00E+00	8,38E-01	0,00E+00	0,00E+00
Materials for energy rec	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	1,43E-02	MND	MND	MND	MND	MND	0,00E+00	MND	0,00E+00	0,00E+00	1,54E-02	0,00E+00	0,00E+00
Exported energy	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	7,63E-02	MND	MND	MND	MND	MND	0,00E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00

ENVIRONMENTAL IMPACTS – EN 15804+A1, CML / ISO 21930

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Global Warming Pot.	kg CO ₂ e	2,52E+01	2,98E-01	1,87E+00	2,73E+01	0,00E+00	2,08E-02	MND	MND	MND	MND	MND	2,75E+02	MND	0,00E+00	5,39E-03	1,93E-01	1,25E-02	-1,33E+01
Ozone depletion Pot.	kg CFC ₁₁ e	7,65E-07	4,87E-08	1,28E-07	9,41E-07	0,00E+00	2,91E-10	MND	MND	MND	MND	MND	7,93E-06	MND	0,00E+00	9,92E-10	3,86E-09	1,04E-09	-3,30E-07
Acidification	kg SO ₂ e	2,20E-01	6,35E-03	4,89E-03	2,31E-01	0,00E+00	1,70E-05	MND	MND	MND	MND	MND	1,19E+00	MND	0,00E+00	1,79E-05	5,22E-04	6,03E-05	-1,16E-01
Eutrophication	kg PO ₄ ³ e	6,73E-02	7,29E-04	3,55E-03	7,16E-02	0,00E+00	1,42E-04	MND	MND	MND	MND	MND	5,18E-01	MND	0,00E+00	4,08E-06	1,90E-04	1,08E-04	-3,36E-02
POCP (“smog”)	kg C ₂ H ₄ e	1,12E-02	1,63E-04	2,71E-04	1,16E-02	0,00E+00	4,70E-06	MND	MND	MND	MND	MND	4,78E-02	MND	0,00E+00	6,99E-07	2,42E-05	4,39E-06	-5,81E-03
ADP-elements	kg Sbe	9,98E-04	3,62E-07	8,25E-06	1,01E-03	0,00E+00	4,96E-08	MND	MND	MND	MND	MND	1,31E-03	MND	0,00E+00	1,24E-08	6,59E-06	2,51E-08	-7,47E-05
ADP-fossil	MJ	2,60E+02	3,86E+00	3,18E+01	2,96E+02	0,00E+00	4,21E-02	MND	MND	MND	MND	MND	3,66E+03	MND	0,00E+00	8,17E-02	9,02E-01	1,62E-01	-1,33E+02

ENVIRONMENTAL IMPACTS – GWP-GHG - THE INTERNATIONAL EPD SYSTEM

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP-GHG ⁹⁾	kg CO ₂ e	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	MND	MND	MND	MND	MND	MND	MND	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00

9) This indicator includes all greenhouse gases excluding biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product as defined by IPCC AR 5 (IPCC 2013). In addition, the characterisation factors for the flows - CH₄ fossil, CH₄ biogenic and Dinitrogen monoxide - were updated in line with the guidance of IES PCR 1.2.5 Annex 1. This indicator is identical to the GWP-total of EN 15804:2012+A2:2019 except that the characterization factor for biogenic CO₂ is set to zero.

VERIFICATION STATEMENT

VERIFICATION PROCESS FOR THIS EPD

This EPD has been verified in accordance with ISO 14025 by an independent, third-party verifier by reviewing results, documents and compliancy with reference standard, ISO 14025 and ISO 14040/14044, following the process and checklists of the program operator for:

- This Environmental Product Declaration
- The Life-Cycle Assessment used in this EPD
- The digital background data for this EPD

Why does verification transparency matter? Read more online

This EPD has been generated by One Click LCA EPD generator, which has been verified and approved by the EPD Hub.

THIRD-PARTY VERIFICATION STATEMENT

I hereby confirm that, following detailed examination, I have not established any relevant deviations by the studied Environmental Product Declaration (EPD), its LCA and project report, in terms of the data collected and used in the LCA calculations, the way the LCA-based calculations have been carried out, the presentation of environmental data in the EPD, and other additional environmental information, as present with respect to the procedural and methodological requirements in ISO 14025:2010 and reference standard.

I confirm that the company-specific data has been examined as regards plausibility and consistency; the declaration owner is responsible for its factual integrity and legal compliance.

I confirm that I have sufficient knowledge and experience of construction products, this specific product category, the construction industry, relevant standards, and the geographical area of the EPD to carry out this verification.

I confirm my independence in my role as verifier; I have not been involved in the execution of the LCA or in the development of the declaration and have no conflicts of interest regarding this verification.

Abderazak Guiz, an authorized verifier acting for EPD Hub Limited.

14.03.2025



ANNEX 1: PEP EXTRAPOLATION COEFFICIENTS OF TOTAL NOCTA FAMILY

Extrapolation rules have been calculated according to PSR-0014-ED2-EN-2023 07 13.

The extrapolation coefficients are calculated at product level. The functional unit coefficient is also available.

$$\text{Extrapolation coefficient at the product level} \times \left(\frac{\text{Lighting output of reference product (lumen)}}{\text{Lighting output of product concerned (lumen)}} \right)$$

Table with information to calculate the extrapolation coefficients

Mass code	Description	product weight (kg)	packaging weight (kg)	Total weight (kg)	Control gear weight (kg)	Class	IP	Luminaire lumen (lm)	Luminaire power (W)
30111 XXX0	NOCTA RD80 VWFL	1,2	0,12	1,32	0,0633	I	IP65	448	7
30111 XXX5 (reference)	NOCTA RD80 VWFL DIM5	1,16	0,16	1,32	0,095	I	IP65	448	7
30112 XXX0	NOCTA RD80 SP	1,2	0,12	1,32	0,045	I	IP65	394	5
30113 XXX0	NOCTA RD80 WFL	1,2	0,12	1,32	0,045	I	IP65	312	5
30114 XXX0	NOCTA RD80 DOWN-UP VWFL	1,4	0,251	1,651	0,1	I	IP65	896	13
30114 XXX5	NOCTA RD80 DOWN-UP VWFL DIM5	1,4	0,28	1,68	0,094	I	IP65	896	13
30115 XXX0	NOCTA RD80 DOWN-UP SP	1,4	0,28	1,68	0,0633	I	IP65	788	9
30115 XXX5	NOCTA RD80 DOWN-UP SP DIM5	1,4	0,28	1,68	0,094	I	IP65	788	9
30116 XXX0	NOCTA RD80 DOWN-UP WFL	1,4	0,28	1,68	0,0633	I	IP65	625	9
30116 XXX5	NOCTA RD80 DOWN-UP WFL DIM5	1,4	0,28	1,68	0,094	I	IP65	625	9
30117 XXX0	NOCTA SQ85 VWFL	1,2	0,24	1,44	0,045	I	IP65	448	7
30117 XXX5	NOCTA SQ85 VWFL DIM5	1,2	0,24	1,44	0,095	I	IP65	448	7
30118 XXX0	NOCTA SQ85 SP	1,2	0,24	1,44	0,045	I	IP65	394	5
30119 XXX0	NOCTA SQ85 WFL	1,2	0,24	1,44	0,045	I	IP65	312	5
30120 XXX0	NOCTA SQ85 DOWN-UP VWFL	1,4	0,28	1,68	0,1	I	IP65	896	13
30120 XXX5	NOCTA SQ85 DOWN-UP VWFL DIM5	1,4	0,28	1,68	0,094	I	IP65	896	13
30121 XXX0	NOCTA SQ85 DOWN-UP SP	1,4	0,28	1,68	0,0633	I	IP65	788	9
30121 XXX5	NOCTA SQ85 DOWN-UP SP DIM5	1,326	0,142	1,468	0,094	I	IP65	788	9
30122 XXX0	NOCTA SQ85 DOWN-UP WFL	1,4	0,28	1,68	0,0633	I	IP65	625	9
30122 XXX5	NOCTA SQ85 DOWN-UP WFL DIM5	1,326	0,142	1,468	0,094	I	IP65	625	9
30123 XXX0	NOCTA SQ155 VWFL	1,8	0,36	2,16	0,045	I	IP65	448	7
30123 XXX5	NOCTA SQ155 VWFL DIM5	1,8	0,36	2,16	0,095	I	IP65	448	7
30124 XXX0	NOCTA SQ155 2VWFL	1,8	0,36	2,16	0,045	I	IP65	142	5
30126 XXX0	NOCTA SQ155 SP	1,8	0,36	2,16	0,045	I	IP65	747	9

30127 XXX0	NOCTA SQ155 WFL	1,8	0,36	2,16	0,045	I	IP65	686	9
30128 XXX0	NOCTA SQ155 DOWN-UP VWFL	2	0,4	2,4	0,1	I	IP65	896	13
30128 XXX5	NOCTA SQ155 DOWN-UP VWFL DIM5	2	0,4	2,4	0,094	I	IP65	896	13
30129 XXX0	NOCTA SQ155 DOWN-UP 2VWFL	2	0,4	2,4	0,0633	I	IP65	285	9
30129 XXX5	NOCTA SQ155 DOWN-UP 2VWFL DIM5	2	0,4	2,4	0,094	I	IP65	285	9
30131 XXX0	NOCTA SQ155 DOWN-UP SP	2	0,4	2,4	0,0633	I	IP65	1493	18
30131 XXX5	NOCTA SQ155 DOWN-UP SP DIM5	2	0,4	2,4	0,094	I	IP65	1493	18
30132 XXX0	NOCTA SQ155 DOWN-UP WFL	2	0,4	2,4	0,0633	I	IP65	1372	18
30132 XXX5	NOCTA SQ155 DOWN-UP WFL DIM5	2	0,4	2,4	0,094	I	IP65	1372	18

Applicable extrapolation coefficients:

		A1-A3	A4	A5	B6	C1-C4	D
Mass code	Extrapol. FU	Fabrication stage	Distribution stage	Installation stage	Use stage	EOL stage	Benefits beyond the system
30111 XXX0	1,000	1,034	1,000	0,750	2,000	1,000	1,034
30111 XXX5	1,000	1,000	1,000	1,000	1,000	1,000	1,000
30112 XXX0	1,137	1,034	1,000	0,750	1,429	1,000	1,034
30113 XXX0	1,436	1,034	1,000	0,750	1,429	1,000	1,034
30114 XXX0	0,500	1,569	1,251	1,569	3,714	1,251	1,569
30114 XXX5	0,500	1,750	1,273	1,750	1,857	1,273	1,750
30115 XXX0	0,569	1,750	1,273	1,750	2,571	1,273	1,750
30115 XXX5	0,569	1,750	1,273	1,750	1,286	1,273	1,750
30116 XXX0	0,717	1,750	1,273	1,750	2,571	1,273	1,750
30116 XXX5	0,717	1,750	1,273	1,750	1,286	1,273	1,750
30117 XXX0	1,000	1,500	1,091	1,500	2,000	1,091	1,500
30117 XXX5	1,000	1,500	1,091	1,500	1,000	1,091	1,500
30118 XXX0	1,137	1,500	1,091	1,500	1,429	1,091	1,500
30119 XXX0	1,436	1,500	1,091	1,500	1,429	1,091	1,500
30120 XXX0	0,500	1,750	1,273	1,750	3,714	1,273	1,750
30120 XXX5	0,500	1,750	1,273	1,750	1,857	1,273	1,750
30121 XXX0	0,569	1,750	1,273	1,750	2,571	1,273	1,750
30121 XXX5	0,569	1,143	1,112	0,887	1,286	1,112	1,143
30122 XXX0	0,717	1,750	1,273	1,750	2,571	1,273	1,750
30122 XXX5	0,717	1,143	1,112	0,887	1,286	1,112	1,143
30123 XXX0	1,000	2,250	1,636	2,250	2,000	1,636	2,250
30123 XXX5	1,000	2,250	1,636	2,250	1,000	1,636	2,250
30124 XXX0	3,155	2,250	1,636	2,250	1,429	1,636	2,250
30126 XXX0	0,600	2,250	1,636	2,250	2,571	1,636	2,250
30127 XXX0	0,653	2,250	1,636	2,250	2,571	1,636	2,250
30128 XXX0	0,500	2,500	1,818	2,500	3,714	1,818	2,500
30128 XXX5	0,500	2,500	1,818	2,500	1,857	1,818	2,500
30129 XXX0	1,572	2,500	1,818	2,500	2,571	1,818	2,500
30129 XXX5	1,572	2,500	1,818	2,500	1,286	1,818	2,500
30131 XXX0	0,300	2,500	1,818	2,500	5,143	1,818	2,500
30131 XXX5	0,300	2,500	1,818	2,500	2,571	1,818	2,500
30132 XXX0	0,327	2,500	1,818	2,500	5,143	1,818	2,500
30132 XXX5	0,327	2,500	1,818	2,500	2,571	1,818	2,500

Explanation used coefficients from PSR-0014-ED2-EN-2023 07 13:

Fabrication stage (A1-A3) extrapolation coefficient:

Maximum value out of formulas described in 3.6.3 Extrapolation rules applied to fabrication stage (A1-A3)

Distribution stage (A4) extrapolation coefficient:

Value out of formula described in 3.6.4 Extrapolation rules applied to distribution stage (A4)

Installation stage (A5) extrapolation coefficient:

Value out of formula described in 3.6.5 Extrapolation rules applied to installation stage (A5)

Use stage (B1 – B7) extrapolation coefficient:

Maximum value out of formulas described in 3.6.6. Extrapolation rules applied to use stage (B1 to B7)

(B2 is not declared in our case, so the formula of B6 applies)

End of life stage (C1 to C4) extrapolation coefficient:

Value out of formula described in 3.6.7. Extrapolation rules applied to end-of-life stage (C1 to C4)

Benefits (D) extrapolation coefficient:

Maximum value out of formulas described in 3.6.8. Extrapolation rules applied to net benefits beyond the system boundaries stage (D) (optional)