
DELTALIGHT




BOXY XL R 93020 DIM1

REFERENCE 251 71 21 931 ED1 W-W

AVAILABLE IN
BLACK-BLACK 251 71 21 931 ED1 B-B
WHITE-BLACK 251 71 21 931 ED1 W-B
WHITE-WHITE 251 71 21 931 ED1 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.5
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-20° INCL.DIMMABLE LED POWER SUPPLY 700mA-DC

Electrical info	
ELECTRICAL	120-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	1-10V
ENERGY CLASS	C
CERTIFICATES	CB, ENEC, LCA, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 23,2W / CRI>90 (R9: 52) / 3000K / 3169lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	3169lm // 23,2W // 136lm/W
LED TECHNICS (LUMINAIRE)	2756lm // 26,7W // 103lm/W

Accessories

HONEYCOMB 78
SOFTENING LENS 78
GLASS SBL 78

For detailed installation instructions, please consult the manual : **251_71_21_XXX_ED1_HAND.pdf**


DELTALIGHT

BOXY XL R 93020 DIM1

251 71 21 931 ED1 W-W

FINISH YOUR SPECIFICATION

Miscellaneous control equipment




300 90 016 ED1 WIRELESS CONTROL 5A DIM1

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 86

☐


Light altering devices



201 02 01 B HONEYCOMB 78 B ☐



201 02 04 SOFTENING LENS 78 ☐



201 02 05 GLASS SBL 78 ☐

Notes: