DELTALIGHT



OML50 - LED ARRAY D TW 1640mm 950 DIM5

REFERENCE 31028 9005

View on website

General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.5
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	@ 2700K: LED cluster 37,2W / CRI>90 (R9: 50) / 2700K-5000K / 4880lm Or @ 5000K: LED cluster 33,8W / CRI>90 (R9: 50) / 2700K-5000K / 5840lm
SDCM	SDCM3
RISKGROUP	RG1
LED TECHNICS (LIGHT SOURCE)	@ 2700K: 4880lm // 37,2W // 131lm/W Or @ 5000K: 5840lm // 33,8W // 173lm/W

Options

WIRELESS CONTROL DIM5

Notes: