




## M26L - SPY 39 WALLWASH SOFT 930 DIM5


23436 9005 BRCU

AVAILABLE IN

**BLACK** 23436 9005 B  
**BRUSHED ALU** 23436 9005 BRA  
**BRUSHED ANTHRACITE** 23436 9005 BRAT  
**BRUSHED COPPER** 23436 9005 BRCU  
**BRUSHED GOLD** 23436 9005 BRG  
**BRUSHED OLD BRONZE** 23436 9005 BROB  
**FLEMISH BRONZE** 23436 9005 FBR  
**FLEMISH GOLD** 23436 9005 FG  
**GOLD COLOURED** 23436 9005 GC  
**WHITE** 23436 9005 W



0-85°/355°



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Low voltage systems Low voltage system mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.3
<b>ADJUSTABILITY</b>	0° to 85° swiveling, 360° rotatable
<b>INFORMATION</b>	WALLWASH LENS EXCL.LED POWER SUPPLY 48V-DC

### Electrical info

<b>ELECTRICAL</b>	48V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	DALI
<b>ENERGY CLASS</b>	F

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
<b>TM-30 VALUES</b>	rf: 90 / Rg: 99
<b>SDCM</b>	SDCM2
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>LED TECHNICS (LIGHT SOURCE)</b>	623lm // 6W // 105lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	341lm // 6,9W // 49lm/W

### Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [23436\\_XXX5\\_HAND.pdf](#)

# DELTALIGHT

## M26L - SPY 39 WALLWASH SOFT 930 DIM5

23436 9005 BRCU

### FINISH YOUR SPECIFICATION

#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

8


Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

20

Dimtype: non-dimmable



**21012 0230** LED POWER SUPPLY 48V-DC / 100W

8

Dimtype: non-dimmable

Cutout dimension (mm): 40



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

17


Dimtype: non-dimmable

Cutout dimension (mm): 40


### COMPATIBLE COMPOSABLES

#### SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


#### Available Colours



**23358 0000** SLM26L - PROFILE



**23358 0010** SLM26L - PROFILE 1m



**23358 0020** SLM26L - PROFILE 2m



# DELTALIGHT

## M26L - SPY 39 WALLWASH SOFT 930 DIM5

23436 9005 BRCU



**23358 0030** SLM26L - PROFILE 3m



Notes: