
DELTALIGHT




DOT.COM L WALLWASH 08 ST 927 HO

REFERENCE 11523 9200 W-B

AVAILABLE IN
BLANC-NOIR 11523 9200 W-B





View on website

General info	
LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	rectangle - 824 x 40
RECESSED DEPTH (MM)	50
THICKNESS OF MOUNTING SURFACE (MM)	min.10
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.8
ADJUSTABILITY	non réglable
INFORMATION	EXCL.LED POWER SUPPLY 500mA-DC

Electrical info	
CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	E
CERTIFICATION	CB, ENEC, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED flex 18W / CRI>90 (R9: 60) / 2700K / 2240lm
SDMC	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	2240lm // 18W // 124lm/W
LED TECHNICS (LUMINAIRE)	1298lm // 21W // 63lm/W

Requirements

LED POWER SUPPLY 500mA-DC DIM

For detailed installation instructions, please consult the manual : **11523_9200_HAND.pdf**

DOT.COM L WALLWASH 08 ST 927 HO


11523 9200 W-B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 **System ceiling**	-
 **Plasterboard**	-
 **Stucanet**	-
 **Wood**	-
 **Concrete**	-
 **Concrete + plaster**	-
 **Lintel + plaster**	-
 **Hollow-core slab**	-
 **Hollow-core slab + plaster**	-
 **Stretched ceiling**	-

FINISH YOUR SPECIFICATION

les batteries de secours



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B










Cutout dimension (mm): 27

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

DOT.COM L WALLWASH 08 ST 927 HO

11523 9200 W-B


les alimentations led

		# of Fixtures
web2print_power_supply_info_box		Min current | Max current
	**300 48 500 ED1** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1 **Dimtype: 1 à 10 V** **Cutout dimension (mm): 30**	1
	**300 48 500 ED5** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 **Dimtype: DALI** **Cutout dimension (mm): 45**	1
	**300 48 500 MDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL **Dimtype: non dimmable** **Cutout dimension (mm): 30**	1
	**300 48 500 WDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL **Dimtype: WDL = dimmable sans fil** **Cutout dimension (mm): 45**	1
	**300 90 61** LED POWER SUPPLY MULTI-POWER DIM6 **Dimtype: fin de phase ou bouton poussoir** **Cutout dimension (mm): 56**	1
	**300 90 63** LED POWER SUPPLY MULTI-POWER DIM9 **Dimtype: 1 à 10 V ou DALI ou boutton poussoir** **Cutout dimension (mm): 82**	2(1)
	**300 90 64** LED POWER SUPPLY MULTI-POWER DIM7 **Dimtype: 1 à 10 V ou bouton poussoir** **Cutout dimension (mm): 72**	1(0)
	**300 90 68** LED POWER SUPPLY MULTI-POWER DIM5 **Dimtype: DALI** **Cutout dimension (mm): 72**	1(0)
	**300 90 69** LED POWER SUPPLY MULTI-POWER HV DIM9 **Dimtype: 1 à 10 V ou DALI ou boutton poussoir** **Cutout dimension (mm): 84**	3(2)

DELTALIGHT

DOT.COM L WALLWASH 08 ST 927 HO

11523 9200 W-B



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 1(0)

Dimtype: 1 à 10 V ou bouton poussoir


Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 1(0)

Dimtype: DALI


Cutout dimension (mm): 55



300 90 135 LED POWER SUPPLY MULTI-POWER HV 2

Dimtype: non dimmable


Cutout dimension (mm): 90



21012 0010 LED POWER SUPPLY MULTI POWER 1

Dimtype: non dimmable


Cutout dimension (mm): 50



21012 0021 LED POWER SUPPLY MULTI POWER DIM1 1

Dimtype: 1 à 10 V


Cutout dimension (mm): 54



21012 0035 LED POWER SUPPLY MULTI POWER DIM5 1

Dimtype: DALI


Cutout dimension (mm): 54



21012 004W LED POWER SUPPLY MULTI-POWER WDL 2(1)

Dimtype: WDL = dimmable sans fil


Cutout dimension (mm): 84



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL 1

Dimtype: WDL = dimmable sans fil


Cutout dimension (mm): 54



21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 1

Dimtype: fin de phase

Cutout dimension (mm): 55



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 1


Dimtype: fin de phase

Cutout dimension (mm): 48

DELTALIGHT

DOT.COM L WALLWASH 08 ST 927 HO

11523 9200 W-B



21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 1

Dimtype: DALI

Cutout dimension (mm): 30

Notes: