DELTALIGHT

HEDRA 451 C 93040 DIM8

REFERENCE 472 221 932 ED8 BBR

AVAILABLE IN
BLACK 472 221 932 ED8 B
BLACK BRONZE 472 221 932 ED8 BBR
GOLD COLOURED 472 221 932 ED8 GC
WHITE 472 221 932 ED8 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WFL-40° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC INCL.1 x CABLE 2 x 0.75mm² / 1,6m

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6,4W / CRI>90 / 3000K / 587lm
SDCM	SDCM2
RISKGROUP	RG1
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	587lm // 6,4W // 92lm/W
LED TECHNICS (LUMINAIRE)	488lm // 7,4W // 66lm/W

Requirements

MIDISPY TUBE

Options

CONNECTION TRIMLESS

For detailed installation instructions, please consult the manual : **472_221_XXX_ED8_HAND.pdf**

DELTALIGHT

HEDRA 451 C 93040 DIM8

472 221 932 ED8 BBR

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40

Suspension parts



15229 0010 B CABLE CLAMP B

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)

Finish your product



414 03 00 B	MIDISPY TUBE B
414 03 00 FBR	MIDISPY TUBE FBR
414 03 00 FG	MIDISPY TUBE FG
414 03 00 MMAT	MIDISPY TUBE MMAT
414 03 00 SG	MIDISPY TUBE SG
414 03 00 W	MIDISPY TUBE W

DELTALIGHT

HEDRA 451 C 93040 DIM8

472 221 932 ED8 BBR

Notes: