



SUPERLOOP SLIM DOWN 70 SBL 930

20580 9300 W

AVAILABLE IN


BLACK 20580 9300 B

FLEMISH BRONZE 20580 9300 FBR

FLEMISH GOLD 20580 9300 FG

GOLD COLOURED 20580 9300 GC

WHITE 20580 9300 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL EXCL.LED POWER SUPPLY 500-700mA-DC INCL.3 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 21,2-29,2W / CRI>90 (R9: 59) / 3000K / 2916-3870lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	3870lm // 29,2W // 132lm/W
LED TECHNICS (LUMINAIRE)	1713lm // 33,6W // 51lm/W

Requirements

LED POWER SUPPLY 500 / 700mA-DC DIM
SUPERLOOP POWERBOX L 500mA
SUPERLOOP POWERBOX L/H 700mA

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

SUPERLOOP SLIM DOWN 70 SBL 930

20580 9300 W

For detailed installation instructions, please consult the manual : [20580_XXX0_HAND.pdf](#)



FINISH YOUR SPECIFICATION

Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

LED power supplies


of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
	300 90 127 LED POWER SUPPLY 500mA-DC / 27W DIM1 Dimtype: 1-10V Cutout dimension (mm): 54	1 ☐
	300 90 128 LED POWER SUPPLY 700mA-DC / 36W DIM1 Dimtype: 1-10V Cutout dimension (mm): 54	1 ☐

DELTALIGHT

SUPERLOOP SLIM DOWN 70 SBL 930


20580 9300 W

	300 90 131 LED POWER SUPPLY 700mA-DC / 38W DIM5	1 ☐
	Dimtype: DALI	
	Cutout dimension (mm): 54	


Power box

of Fixtures


	# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current Max current
---	---	---------------------------

	321 55 205 ED1 B SUPERLOOP POWERBOX L 500mA DIM1 B	1 ☐
	Dimtype: 1-10V	

	321 55 205 ED1 W SUPERLOOP POWERBOX L 500mA DIM1 W	1 ☐
--	---	----------------------------


	321 55 207 ED1 B SUPERLOOP POWERBOX L 700mA DIM1 B	1 ☐
	Dimtype: 1-10V	

	321 55 207 ED1 W SUPERLOOP POWERBOX L 700mA DIM1 W	1 ☐
--	---	----------------------------

	321 55 307 ED5 B SUPERLOOP POWERBOX H8 700mA DIM5 B	1 ☐
	Dimtype: DALI	

	321 55 307 ED5 W SUPERLOOP POWERBOX H8 700mA DIM5 W	1 ☐
--	--	----------------------------

Coversets

	204 00 62 ANO COVERSET R 62 ANO	☐
---	--	--------------------------

	204 00 62 B COVERSET R 62 B	☐
--	------------------------------------	--------------------------

	204 00 62 W COVERSET R 62 W	☐
--	------------------------------------	--------------------------

DELTALIGHT

SUPERLOOP SLIM DOWN 70 SBL 930

20580 9300 W



	<u>204 00 90 ANO</u> COVERSET R 90 ANO	☐
	<u>204 00 90 B</u> COVERSET R 90 B	☐
	<u>204 00 90 W</u> COVERSET R 90 W	☐
	<u>204 00 100 ANO</u> COVERSET R 100 ANO	☐
	<u>204 00 100 B</u> COVERSET R 100 B	☐
	<u>204 00 100 W</u> COVERSET R 100 W	☐
	<u>204 62 62 ANO</u> COVERSET S 62 ANO	☐
	<u>204 62 62 B</u> COVERSET S 62 B	☐
	<u>204 62 62 W</u> COVERSET S 62 W	☐
	<u>204 80 80 ANO</u> COVERSET S 80 ANO	☐
	<u>204 80 80 B</u> COVERSET S 80 B	☐
	<u>204 80 80 W</u> COVERSET S 80 W	☐
	<u>204 90 90 ANO</u> COVERSET S 90 ANO	☐
	<u>204 90 90 B</u> COVERSET S 90 B	☐
	<u>204 90 90 W</u> COVERSET S 90 W	☐

DELTA LIGHT


SUPERLOOP SLIM DOWN 70 SBL 930

20580 9300 W

Suspension parts

	328 10 01 SUSPENSION TRIMLESS O.F.A.	☐
Cutout dimension (mm): 62 (CONCRETE: 102)		
	15225 0340 B SUSPENSION ST B	☐
Cutout dimension (mm): 27		
15225 0340 W SUSPENSION ST W		☐

Electric connection parts

	328 10 03 CONNECTION TRIMLESS O.F.A.	☐
Cutout dimension (mm): 62 (CONCRETE: 102)		
	15225 0360 B CONNECTION ST B	☐
Cutout dimension (mm): 43		
15225 0360 W CONNECTION ST W		☐

Notes: