





ZOOVER 140 DOWN-UP LIGHT GREY 930 DIM4

28221 9304 B

AVAILABLE IN
NOIR 28221 9304 B



[View on website](#)



General info	
LOCATION	interieur
INSTALLATION	Plafond Suspendu
INGRESS PROTECTION	IP20
WEIGHT (KG)	6.5
ADJUSTABILITY	non réglable
INFORMATION	INCL.PC SBL INCL.DIMMABLE LED POWER SUPPLY INCL.3 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 5 x 0.75mm ²
Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	DALI ou DSI ou bouton poussoir
ENERGY CLASS	E
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 34,4W / CRI>90 (R9: 68) / 3000K / 4767lm UP: LED cluster 5,1W / CRI>90 (R9: 68) / 3000K / 706lm
RVALUES	Rf: 89 / Rg: 97
SDMC	SDCM3
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 4767lm // 34,4W // 139lm/W UP: 706lm // 5,1W // 139lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 3842lm // 39,6W // 97lm/W UP: 668lm // 5,9W // 114lm/W

Remarks

[Click here for ZOOVER 140 acoustic specifications](#)

Options

CABLE BASE R / S

COVERSET R 62-90-100

CONNECTION ST / CONNECTION TRIMLESS

SUSPENSION ST / SUSPENSION TRIMLESS

DELTA LIGHT


ZOOVER 140 DOWN-UP LIGHT GREY 930 DIM4

28221 9304 B



For detailed installation instructions, please consult the manual : [28221_XXX4_HAND.pdf](#)

FINISH YOUR SPECIFICATION

le cable d'alimentation

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

les sets pour recouvrement plafond

	204 00 62 ANO COVERSET R 62 ANO	☐
	204 00 62 B COVERSET R 62 B	☐
	204 00 62 W COVERSET R 62 W	☐
	204 00 90 ANO COVERSET R 90 ANO	☐

DELTALIGHT


ZOOVER 140 DOWN-UP LIGHT GREY 930 DIM4

28221 9304 B

204 00 90 B COVERSET R 90 B

☐

204 00 90 W COVERSET R 90 W

☐

204 00 100 ANO COVERSET R 100 ANO

☐


204 00 100 B COVERSET R 100 B

☐

204 00 100 W COVERSET R 100 W

☐


les accessoires de suspension



328 10 01 SUSPENSION TRIMLESS O.F.A.

☐

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0340 B SUSPENSION ST B


☐

Cutout dimension (mm): 27

15225 0340 W SUSPENSION ST W

☐

les accessoires pour connexions électriques



328 10 03 CONNECTION TRIMLESS O.F.A.

☐

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B

☐

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

☐

DELTALIGHT

ZOOVER 140 DOWN-UP LIGHT GREY 930 DIM4

28221 9304 B

Notes: