





M26L - SPY 39 WALLWASH SOFT
930 DIM5

23436 9005 BROB

- AVAILABLE IN
- BLACK 23436 9005 B
 - BRUSHED ALU 23436 9005 BRA
 - BRUSHED ANTHRACITE 23436 9005 BRAT
 - BRUSHED COPPER 23436 9005 BRCU
 - BRUSHED GOLD 23436 9005 BRG
 - BRUSHED OLD BRONZE 23436 9005 BROB
 - FLEMISH BRONZE 23436 9005 FBR
 - FLEMISH GOLD 23436 9005 FG
 - GOLD COLOURED 23436 9005 GC
 - WHITE 23436 9005 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 360° rotatable
INFORMATION	WALLWASH LENS EXCLLED POWER SUPPLY 48V-DC
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	EPD
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	341lm // 6,9W // 49lm/W
Requirements	
LED POWER SUPPLY 48V-DC	

For detailed installation instructions, please consult the manual : [23436_XXX5_HAND.pdf](#)

M26L - SPY 39 WALLWASH SOFT 930 DIM5

23436 9005 BROB

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
5510090 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable	8	
63114125 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable	20	
1729830 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40	8	
2239230 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40	17	

COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
3226 23358 0000 SLM26L - PROFILE	
3226 23358 0010 SLM26L - PROFILE 1m	
3226 23358 0020 SLM26L - PROFILE 2m	

DELTALIGHT

M26L - SPY 39 WALLWASH SOFT 930 DIM5

23436 9005 BROB



23358 0030 SLM26L - PROFILE 3m



Notes: