
DELTALIGHT




# MINIGRID ON 150 93018 DIM8

**REFERENCE** 100044 9318 W-B

AVAILABLE IN
**BLACK-BLACK** 100044 9318 B-B
**BLACK-WHITE** 100044 9318 B-W
**WHITE-BLACK** 100044 9318 W-B
**WHITE-WHITE** 100044 9318 W-W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Ceiling Surface mounted |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 1.1 |
| **ADJUSTABILITY** | 0° to 20° swiveling, 350° rotatable |
| **INFORMATION** | REFLECTOR SP-18°<br>INCL.DIMMABLE LED POWER SUPPLY 500mA-DC |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 220-240V / 50-60Hz |
| **CLASS** | II |
| **POWER SUPPLY** | YES |
| **DIM TYPE** | mains (phase cut-off) |
| **ENERGY CLASS** | E |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm |
| **TM-30 VALUES** | Rf: 90 / Rg: 99 |
| **SDCM** | SDCM1 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 18° |
| **LED TECHNICS (LIGHT SOURCE)** | 1089lm // 8,6W // 127lm/W |
| **LED TECHNICS (LUMINAIRE)** | 903lm // 9,9W // 91lm/W |

For detailed installation instructions, please consult the manual : **100044_XXX8_HAND.pdf**


DELTALIGHT

# MINIGRID ON 150 93018 DIM8

100044 9318 W-B

## FINISH YOUR SPECIFICATION

### Miscellaneous control equipment




**300 90 004 ED8** WIRELESS CONTROL DIM8

**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 40**

Notes: