
DELTALIGHT




M20/M26H - SPY 66 93030 DIM5

REFERENCE 23328 9325 W

AVAILABLE IN
BLACK 23328 9325 B
WHITE 23328 9325 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCL.LED POWER SUPPLY 48V-DC Optional REFLECTORS 18° & 45° available

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 25W / CRI>90 (R9: 52) / 3000K / 2811lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	2811lm // 25W // 112lm/W
LED TECHNICS (LUMINAIRE)	1937lm // 28,8W // 67lm/W

Remarks

Take a look at our MAGNETIC PROFILES movie

Requirements

SPY 66 TUBE
LED POWER SUPPLY 48V-DC

Accessories

HONEYCOMB 57

DELTALIGHT

M20/M26H - SPY 66 93030 DIM5

23328 9325 W

For detailed installation instructions, please consult the manual : **23328_XXX5_HAND.pdf**


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures


of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 3

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 8


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 3

Dimtype: non-dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W — 7

Dimtype: non-dimmable

Cutout dimension (mm): 40

Light altering devices




24611 0150 B HONEYCOMB 57 SINGLE USE B

M20/M26H - SPY 66 93030 DIM5

23328 9325 W

Finish your product



24611 0100 B SPY 66 TUBE B

24611 0100 FBR SPY 66 TUBE FBR

24611 0100 FG SPY 66 TUBE FG

24611 0100 GC SPY 66 TUBE GC

24611 0100 W SPY 66 TUBE W

Replaceable reflector / lens



24611 0220 SPY 66 REFLECTOR 18°



24611 0230 SPY 66 REFLECTOR 30°



24611 0240 SPY 66 REFLECTOR 45°

COMPATIBLE COMPOSABLES

SHIFTLINE M26H + SBL

Available Colours



30411 9205 SHIFTLINE M26H + SBL 2m DIM5


DELTALIGHT

M20/M26H - SPY 66 93030 DIM5


23328 9325 W




30411 9305 SHIFTLINE M26H + SBL 2m DIM5




30412 9205 SHIFTLINE M26H + SBL 3m DIM5



30412 9305 SHIFTLINE M26H + SBL 3m DIM5




30413 9205 SHIFTLINE M26H + SBL 4m DIM5




30413 9305 SHIFTLINE M26H + SBL 4m DIM5

SHIFTLINE M26H profile


Available Colours




23359 0000 SLM26H - PROFILE



23359 0010 SLM26H - PROFILE 1m



23359 0020 SLM26H - PROFILE 2m







23359 0030 SLM26H - PROFILE 3m

DELTALIGHT

M20/M26H - SPY 66 93030 DIM5

23328 9325 W

SPLITLINE M20 ST profile		Available Colours
	**23397 0000** SPM20 ST - PROFILE	
	**23397 0020** SPM20 ST - PROFILE 2m	
	**23397 0030** SPM20 ST - PROFILE 3m	

SPLITLINE M20 profile		Available Colours
	**420 20 10 00** SPM20 - PROFILE 1m	
	**420 20 20 00** SPM20 - PROFILE 2m	
	**420 20 30 00** SPM20 - PROFILE 3m	
	**23301 0000** SPM20 - PROFILE B	

Notes: