

DEEP RINGO X



The conical shaped reflector of the Deep Ringo fixtures and the deeper placed LED light, make sure that glare is reduced to a minimum when Deep Ringo is installed in the ceiling. The small trim at the end of the reflector gives a refined touch to this elegant luminaire. In full IP65, Deep Ringo X boasts Deltalight's robust exterior finish. In the standard size or mini, Deep Ringo will coordinate seamlessly with the interior Deep Ringo range.

Specification	Std X	Mini X
LED Aperture:	1 ⁵ / ₁₆ "	1 ¹ / ₈ "
Ceiling Cut-out:	3"	2 ³ / ₁₆ "
Ceiling Thickness:	Min. ³ / ₁₆ "	
Adjustability:	Fixed	
Rating:	IP65 (Wet)	

Performance	Std X	Mini X
LED Maintenance:	L90>50,000h	
McAdam Step:	1	
CRI:	90	
*SP:	10W	6.1W
*HP:	14W	10W
**Standard Optic:	33°	37°

Delivered Lumens	2700K	3000K	3500K
Deep Ringo S X SP:	768Lm	803Lm	832Lm
Deep Ringo S X HP:	1035Lm	1082Lm	1121Lm
Deep Ringo Mini X SP:	468Lm	488Lm	507Lm
Deep Ringo Mini X HP:	649Lm	678Lm	703Lm

Listing

ETL certified to US and Canadian safety standards.

Warranty

5-year limited warranty.

Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: DRGR-MFX-STIAT_RMTD1-277-HPS30-B

Luminaire	Shape	Style	Function	Rating	Installation	Applications	Controls***	Power*	Optic**	CCT	Finish
DRG Deep Ringo	R Round	S Standard	F Fixed	X Exterior finish, IP65 for exterior use	ST Recessed with small trim	IAT ^(1,2) New Construction IC Airtight	D1-120 0-10V dim 120V D1-277 0-10V dim 277V D8-120 FE ELV dim 120V	SP Standard Power HP High Power	S Standard	27 2700K 30 3000K 35 3500K	B Black FBRX Flemish Bronze N Anthracite W White
						NPF New Construction Non-IC Plasterframe					
		M Mini	F Fixed	X Exterior finish, IP65 for exterior use	ST Recessed with small trim	REM Remodel Non-IC					
						IAT ^(1,3) New Construction IC Airtight IAT_RMT ⁽¹⁾ New Construction IC Airtight + Remote Power Supply					

1 Provided with UNV driver when using Controls D1.

2 Not available with Power HP.

3 Not available with Power SP.


***Contact factory for Dali, DMX, or other dimming options

Related Products


Deep Ringo (interior)

Finish Options

DEEP RINGO Std X




DEEP RINGO Mini X




Photometric Data

DEEP RINGO Std X




DEEP RINGO Mini X



Installation Options - Style S

IC AIRTIGHT (With Style S)


S-SMALL:
A:12"-5/8 x B:11"-1/16 x C:4"-13/16
A:323mm x B:281mm x C:122mm



- Low Profile under 5" Height
- New Construction Airtight
- For use in insulated ceiling
- Chicago Plenum
- ETL Listed
- Hangerbar expand to 24"-23/32 or 15"-3/32 - reduce to 12"-23/32 or 9"-1/32
- Damp rated
- Patented System for easy driver servicing from room side

NON-IC PLASTERFRAME (With Style S)


S-SMALL:
A:12"-23/32 x B:11"-1/16 x C:5"
A:323mm x B:281mm x C:127mm



- Low Profile 5" Height
- New Construction
- For use in non-insulated ceiling
- ETL Listed
- Hangerbar expand to 24"-23/32 or 15"-3/32 - reduce to 12"-23/32 or 9"-1/32
- Damp rated
- Voltage dedicated (120V or 277V)

Remodel NON-IC (With Style S)

A:10" x B:1"-3/8 x C:2"
A:254mm x B:35mm x C:50mm




- For Remodel application
- For use in non-insulated ceiling
- ETL Listed
- Damp rated
- Voltage Dedicated (120V or 277V)

Installation Options - Style M

IC AIRTIGHT (With Style M)

S-SMALL:


A: 12"-5/8 x B: 11"-1/16 x C: 4"-13/16
A: 323mm x B: 281mm x C: 122mm



- Low Profile under 5" Height
- New Construction Airtight
- For use in insulated ceiling
- Chicago Plenum
- ETL Listed
- Hangerbar expand to 24"-23/32 or 15"-3/32 - reduce to 12"-23/32 or 9"-1/32
- Damp rated
- Patented System for easy driver servicing from room side

Remote Driver (For Style M with Controls D8)


A: 8" x B: 2"-1/2 x C: 2"-1/2
A: 203mm x B: 64mm x C: 64mm



- For Remote application
- ETL Listed
- Damp rated

Remote Driver (For Style M with Controls D1)

A: 8" x B: 2"-3/16 x C: 4"-1/4
A: 203mm x B: 72mm x C: 108mm



- For Remote application
- ETL Listed
- Damp rated

Driver Options

D1

- | | |
|----------------------------|---|
| • Dimming Control | 0-10V |
| • Dimming Range | 1-100% |
| • Dim to off | yes at 0.8V, 1V, 1.2V, or N/A |
| • Power Factor @ Full Load | >0.9 under 120Vac Input with 80-100% load condition (for all output currents) |
| • Efficiency @ Full Load | ≥86 |
| • THD @ Full Load | <20% under 120Vac input with 80-100% load condition (for all output currents) |

Dimmer Compatibility

- Leviton IP710-LFZ / IP710-DLX
- Lutron DTV/DVSTV/DVSCSTV/DVSCSTV

D8

- | | |
|----------------------------|---------------|
| • Dimming Control | Phase Control |
| • Dimming Range | 10-100% |
| • Dim to off | no |
| • Power Factor @ Full Load | >0.9 |
| • Efficiency @ Full Load | ≥80 |
| • THD @ Full Load | <5% |

Dimmer Compatibility

- Leviton IPE04-1LZ
- Lutron DVELV-300P

D8 (For Style S Power HP)

- | | |
|----------------------------|---------------|
| • Dimming Control | Phase Control |
| • Dimming Range | 20-100% |
| • Dim to off | yes |
| • Power Factor @ Full Load | >0.95 |
| • Efficiency @ Full Load | ≥80 |
| • THD @ Full Load | <10% |

Dimmer Compatibility

- Leviton IPE04-1LZ
- Lutron DVELV-300P

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.