



COMPO L TW 96550

9 15737 9040 B



AVAILABLE IN

NEGRO 9 15737 9040 B

CHROMO 9 15737 9040 C

CHROMO OSCURO 9 15737 9040 DC

BLANCO 9 15737 9040 W



[View on website](#)



General info

LOCATION	interior
INSTALLATION	Techo Empotrado
CUTOUT SHAPE/SIZE (MM)	redondo - 135
RECESSED DEPTH (MM)	130
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.466
ADJUSTABILITY	0° to 30° giratorio, 355° orientable

Electrical info

CLASS	III
DIM TYPE	dependiendo del tipo de fuente de alimentación externa
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 17,8W / CRI>90 (R9: 50) / 2700K-6500K / 2054lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	50°
LED TECHNICS (LIGHT SOURCE)	2054lm // 17,8W // 116lm/W
LED TECHNICS (LUMINAIRE)	1337lm // 20,5W // 65lm/W

Requirements

LED POWER SUPPLY 500 mA - DC

Accessories

COMPO L HONEYCOMB SINGLE USE B

COMPO L LINEAR SPREAD LENS

COMPO L SPREAD LENS

COMPO L SOFTENING LENS

COMPO L GLASS SBL

For detailed installation instructions, please consult the manual : [9_15737_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required

FINISH YOUR SPECIFICATION

Fuente de alimentación LED

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

15710 6000 LED POWER SUPPLY MULTIPower 20W DALI DT8 500mA

1

Mounting Kit



15710 0030 B MOUNTING KIT COMPO L TRIM B

☐

Cutout dimension (mm): 92

15710 0030 W MOUNTING KIT COMPO L TRIM W

☐

15710 0060 MOUNTING KIT COMPO L TRIMLESS

☐

Cutout dimension (mm): 92

Dispositivos de modificación de Luz

15710 2100 B COMPO L HONEYCOMB SINGLE USE B

☐

15710 2110 COMPO L LINEAR SPREAD LENS

☐

DELTALIGHT

COMPO L TW 96550

9 15737 9040 B

Cutout dimension (mm): 42

15710 2120 COMPO L SPREAD LENS



Cutout dimension (mm): 42

15710 2130 COMPO L SOFTENING LENS



Cutout dimension (mm): 42

15710 2140 COMPO L GLASS SBL



Cutout dimension (mm): 42

Notes: