



OML50 - LED ARRAY DU HO 656mm 930 DIM5

31032 9305



[Bekijk op website](#)



Algemene info	
LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0.8
INFO	CLUSTER DOWN: 3863lm/m CLUSTER UP: 2663lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT
Elektrische info	
INGANGSSPANNING	220-240V / 0 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	DALI
ENERGIE KLASSE	D
CERTIFICATEN	EPD, RCM
Info lichtbron	
LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 16,3W / CRI>90 (R9: 50) / 3000K / 2534lm UP: LED cluster 12,1W / CRI>90 (R9: 50) / 3000K / 1747lm
TM-30-15 WAARDEN	Rf: 92 / Rg: 100
SDCM	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 2534lm // 16,3W // 155lm/W UP: 1747lm // 12,1W // 145lm/W

Opties	
WIRELESS CONTROL DIM5	

Notes: