
DELTALIGHT




# DOT.COM L WALLWASH 08 ST 930 HO

**REFERENCE** 11523 9300 W-B

AVAILABLE IN
**WHITE-BLACK** 11523 9300 W-B



View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Ceiling Recessed |
| **CUTOUT SHAPE/SIZE (MM)** | rectangle - 824 x 40 |
| **RECESSED DEPTH (MM)** | 50 |
| **THICKNESS OF MOUNTING SURFACE (MM)** | min.10 |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 1.8 |
| **ADJUSTABILITY** | non adjustable |
| **INFORMATION** | EXCL.LED POWER SUPPLY 500mA-DC |

| Electrical info | |
|---|---|
| **CLASS** | III |
| **DIM TYPE** | depending on power supply |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, ENEC, LCA |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED flex 18W / CRI>90 (R9: 60) / 3000K / 2240lm |
| **SDCM** | SDCM3 |
| **LM80** | L70 > 30000 |
| **LED TECHNICS (LIGHT SOURCE)** | 2240lm // 18W // 124lm/W |
| **LED TECHNICS (LUMINAIRE)** | 1298lm // 20,7W // 63lm/W |

**Requirements**

LED POWER SUPPLY 500mA-DC DIM

For detailed installation instructions, please consult the manual : **11523_9200_HAND.pdf**

# DOT.COM L WALLWASH 08 ST 930 HO


11523 9300 W-B

## CEILING COMPATIBILITY

| Ceiling Type | Mounting Kit |
|---|---|
|  **System ceiling** | - |
|  **Plasterboard** | - |
|  **Stucanet** | - |
|  **Wood** | - |
|  **Concrete** | - |
|  **Concrete + plaster** | - |
|  **Lintel + plaster** | - |
|  **Hollow-core slab** | - |
|  **Hollow-core slab + plaster** | - |
|  **Stretched ceiling** | - |

## FINISH YOUR SPECIFICATION

### Emergency units




**21032 0270 B** EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B

**Cutout dimension (mm): 27**

**21032 0270 W** EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

DELTALIGHT

# DOT.COM L WALLWASH 08 ST 930 HO


11523 9300 W-B

## LED power supplies

## # of Fixtures

# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


**Min current | Max current**




**300 48 500 ED1** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1 — 1

**Dimtype: 1-10V**


**Cutout dimension (mm): 30**




**300 48 500 ED5** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 — 1

**Dimtype: DALI**


**Cutout dimension (mm): 45**




**300 48 500 MDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL — 1

**Dimtype: non-dimmable**


**Cutout dimension (mm): 30**




**300 48 500 WDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL — 1

**Dimtype: WDL = wireless dimmable**


**Cutout dimension (mm): 45**




**300 90 61** LED POWER SUPPLY MULTI-POWER DIM6 — 1

**Dimtype: mains (phase cut-off) or push button**


**Cutout dimension (mm): 56**




**300 90 63** LED POWER SUPPLY MULTI-POWER DIM9 — 2(1)

**Dimtype: 1-10V or DALI or push button**


**Cutout dimension (mm): 82**




**300 90 64** LED POWER SUPPLY MULTI-POWER DIM7 — 1(0)

**Dimtype: 1-10V or push button**

**Cutout dimension (mm): 72**




**300 90 68** LED POWER SUPPLY MULTI-POWER DIM5 — 1(0)


**Dimtype: DALI**

**Cutout dimension (mm): 72**

DELTALIGHT

# DOT.COM L WALLWASH 08 ST 930 HO


11523 9300 W-B




**300 90 69** LED POWER SUPPLY MULTI-POWER HV DIM9 3(2)

**Dimtype: 1-10V or DALI or push button**


**Cutout dimension (mm): 84**




**300 90 124** LED POWER SUPPLY MULTI-POWER DIM7 1(0)

**Dimtype: 1-10V or push button**


**Cutout dimension (mm): 55**




**300 90 125** LED POWER SUPPLY MULTI-POWER MINI DIM5 1(0)

**Dimtype: DALI**


**Cutout dimension (mm): 55**




**300 90 135** LED POWER SUPPLY MULTI-POWER HV 2

**Dimtype: non-dimmable**


**Cutout dimension (mm): 90**




**21012 0010** LED POWER SUPPLY MULTI POWER 1

**Dimtype: non-dimmable**


**Cutout dimension (mm): 50**




**21012 0021** LED POWER SUPPLY MULTI POWER DIM1 1

**Dimtype: 1-10V**


**Cutout dimension (mm): 54**




**21012 0035** LED POWER SUPPLY MULTI POWER DIM5 1

**Dimtype: DALI**


**Cutout dimension (mm): 54**




**21012 004W** LED POWER SUPPLY MULTI-POWER WDL 2(1)

**Dimtype: WDL = wireless dimmable**


**Cutout dimension (mm): 84**




**21012 005W** LED POWER SUPPLY MULTI-POWER COMPACT WDL 1

**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 54**




**21012 0288** LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 1


**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 55**

DELTALIGHT

# DOT.COM L WALLWASH 08 ST 930 HO


11523 9300 W-B




**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 1

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 48**




**21032 0305** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 1

**Dimtype: DALI**

**Cutout dimension (mm): 30**

Notes: