



EXCLUSIVELY AVAILABLE IN INDIA

## COMPO L TW 94020

### REFERENCE

9 15738 9020 B



### AVAILABLE IN

**BLACK** 9 15738 9020 B

**CHROMED** 9 15738 9020 C

**DARK CHROMED** 9 15738 9020 DC

**WHITE** 9 15738 9020 W



[View on website](#)



### General info

|                                           |                                     |
|-------------------------------------------|-------------------------------------|
| <b>LOCATION</b>                           | indoor                              |
| <b>INSTALLATION</b>                       | Ceiling Recessed                    |
| <b>CUTOUT SHAPE/SIZE (MM)</b>             | round - 135                         |
| <b>RECESSED DEPTH (MM)</b>                | 130                                 |
| <b>THICKNESS OF MOUNTING SURFACE (MM)</b> | max.25                              |
| <b>INGRESS PROTECTION</b>                 | IP20                                |
| <b>WEIGHT (KG)</b>                        | 0.466                               |
| <b>ADJUSTABILITY</b>                      | 0° to 30° swiveling, 355° rotatable |

### Electrical info

|                     |                           |
|---------------------|---------------------------|
| <b>CLASS</b>        | III                       |
| <b>DIM TYPE</b>     | depending on power supply |
| <b>ENERGY CLASS</b> | G                         |

### Lightsource info

|                                    |                                                          |
|------------------------------------|----------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                      |
| <b>LIGHTSOURCE</b>                 | LED array 17,8W / CRI>90 (R9: 50) / 1800K-4000K / 1832lm |
| <b>SDCM</b>                        | SDCM2                                                    |
| <b>RISKGROUP</b>                   | RG1                                                      |
| <b>LM80</b>                        | L90B10 > 50000                                           |
| <b>BEAMANGLE</b>                   | 20°                                                      |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1832lm // 17,8W // 101lm/W                               |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 1053lm // 20,5W // 51lm/W                                |

### Requirements

LED POWER SUPPLY 500 mA - DC

### Accessories

COMPO L HONEYCOMB SINGLE USE B  
COMPO L LINEAR SPREAD LENS  
COMPO L SPREAD LENS  
COMPO L SOFTENING LENS  
COMPO L GLASS SBL

For detailed installation instructions, please consult the manual : [9\\_15738\\_XXX0\\_HAND.pdf](#)

# DELTALIGHT

## COMPO L TW 94020

9 15738 9020 B

### CEILING COMPATIBILITY

| Ceiling Type                                                                     | Mounting Kit                                                                                                                 |          |
|----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|----------|
|  |  15710 0030 - MOUNTING KIT COMPO L TRIM     | Required |
|                                                                                  |  15710 0060 - MOUNTING KIT COMPO L TRIMLESS | Required |
|  |  15710 0030 - MOUNTING KIT COMPO L TRIM     | Required |
|                                                                                  |  15710 0060 - MOUNTING KIT COMPO L TRIMLESS | Required |
|  |  15710 0030 - MOUNTING KIT COMPO L TRIM     | Required |
|                                                                                  |  15710 0060 - MOUNTING KIT COMPO L TRIMLESS | Required |

### FINISH YOUR SPECIFICATION

#### LED Power supply

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

**15710 6000** LED POWER SUPPLY MULTIPOWER 20W DALI DT8 500mA

1

#### Mounting kits



**15710 0030 B** MOUNTING KIT COMPO L TRIM B

Cutout dimension (mm): 92

**15710 0030 W** MOUNTING KIT COMPO L TRIM W



**15710 0060** MOUNTING KIT COMPO L TRIMLESS

Cutout dimension (mm): 92

#### Light altering devices

**15710 2100 B** COMPO L HONEYCOMB SINGLE USE B

**15710 2110** COMPO L LINEAR SPREAD LENS

# DELTALIGHT

## COMPO L TW 94020

9 15738 9020 B

Cutout dimension (mm): 42

**15710 2120**    COMPO L SPREAD LENS



Cutout dimension (mm): 42

**15710 2130**    COMPO L SOFTENING LENS



Cutout dimension (mm): 42

**15710 2140**    COMPO L GLASS SBL



Cutout dimension (mm): 42

Notes: