





iMAX II ROUND ADJUSTABLE MP 92718

24211 9210 W

AVAILABLE IN
NOIR 24211 9210 B
BLANC 24211 9210 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 98
RECESSED DEPTH (MM)	155
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20 or IP54 (with TUBE IP)
WEIGHT (KG)	0.5
ADJUSTABILITY	0° à 30° inclinable, 355° rotatif
INFORMATION	LENS SP-18° EXCLLED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	E
CERTIFICATION	CB, EAC, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,6-17,2W / CRI>90 (R9: 60) / 2700K / 1458-2009lm
RVALUES	rf: 89 / Rg: 100
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	18°
LED TECHNICS (LIGHT SOURCE)	2009lm // 17,2W // 117lm/W
LED TECHNICS (LUMINAIRE)	1387lm // 19,8W // 70lm/W

Requirements

iMAX II TUBE ROUND
 LED POWER SUPPLY 350 / 500mA-DC DIM

Accessories

iMAX II ACCESSOIRES

For detailed installation instructions, please consult the manual : [24211_XXXX_HAND.pdf](#)

iMAX II ROUND ADJUSTABLE MP 92718


24211 9210 W

CEILING COMPATIBILITY



Ceiling Type	Mounting Kit	
 System ceiling	 15215 0010 - MOUNTING KIT FLUSH iMAX II ROUND	Required
 Plasterboard	 15215 0010 - MOUNTING KIT FLUSH iMAX II ROUND	Required
 Stucanet	 15215 0010 - MOUNTING KIT FLUSH iMAX II ROUND	Required
 Wood	-	
 Stretched ceiling	-	

FINISH YOUR SPECIFICATION

les batteries de secours





	21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B	☐
	21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W	☐

les alimentations led

		# of Fixtures
 web2print_power_supply_info_box		Min current Max current
	300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 30	1 ☐
	300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 45	1 ☐

iMAX II ROUND ADJUSTABLE MP 92718

24211 9210 W

	300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL	1	☐
	Dimtype: non dimmable		
	Cutout dimension (mm): 30		
	300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL	1	☐
	Dimtype: WDL = dimmable sans fil		
	Cutout dimension (mm): 45		
	300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1	1	☐
	Dimtype: 1 à 10 V		
	Cutout dimension (mm): 30		
	300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	1	☐
	Dimtype: DALI		
	Cutout dimension (mm): 45		
	300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL	1	☐
	Dimtype: non dimmable		
	Cutout dimension (mm): 30		
	300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL	1	☐
	Dimtype: WDL = dimmable sans fil		
	Cutout dimension (mm): 45		
	300 90 61 LED POWER SUPPLY MULTI-POWER DIM6	1 1	☐
	Dimtype: fin de phase ou bouton poussoir		
	Cutout dimension (mm): 56		
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	2(2) 2(2)	☐
	Dimtype: 1 à 10 V ou DALI ou bouton poussoir		
	Cutout dimension (mm): 82		
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7	1(1) 1(0)	☐
	Dimtype: 1 à 10 V ou bouton poussoir		
	Cutout dimension (mm): 72		
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9	1 -	☐
	Dimtype: 1 à 10 V ou DALI ou bouton poussoir		








iMAX II ROUND ADJUSTABLE MP 92718

24211 9210 W

	<u>300 90 68</u> LED POWER SUPPLY MULTI-POWER DIM5 Dimtype: DALI Cutout dimension (mm): 72	1(1) 1(0) ☐
	<u>300 90 69</u> LED POWER SUPPLY MULTI-POWER HV DIM9 Dimtype: 1 à 10 V ou DALI ou bouton poussoir Cutout dimension (mm): 84	3(3) 3(2) ☐
	<u>300 90 124</u> LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1 à 10 V ou bouton poussoir Cutout dimension (mm): 55	1(1) 1(0) ☐
	<u>300 90 125</u> LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	1(1) 1(0) ☐
	<u>300 90 135</u> LED POWER SUPPLY MULTI-POWER HV Dimtype: non dimmable Cutout dimension (mm): 90	2->2 2 ☐
	<u>21012 0010</u> LED POWER SUPPLY MULTI POWER Dimtype: non dimmable Cutout dimension (mm): 50	1 1 ☐
	<u>21012 0021</u> LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 54	1 1 ☐
	<u>21012 0035</u> LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	1 1 ☐
	<u>21012 004W</u> LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 84	2(2) 2(2) ☐
	<u>21012 005W</u> LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 54	1 1 ☐

iMAX II ROUND ADJUSTABLE MP 92718

24211 9210 W

	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 Dimtype: fin de phase Cutout dimension (mm): 50	1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 Dimtype: fin de phase Cutout dimension (mm): 55	1	☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: fin de phase Cutout dimension (mm): 48	1 1	☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 Dimtype: non dimmable Cutout dimension (mm): 60	1(1)	☐
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 Dimtype: non dimmable Cutout dimension (mm): 60	1(0)	☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 30	1	☐
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 Dimtype: DALI Cutout dimension (mm): 30	1	☐

kit de montage




	15215 0010 MOUNTING KIT FLUSH iMAX II ROUND Cutout dimension (mm): 121		☐
--	--	--	--------------------------

DELTALIGHT



iMAX II ROUND ADJUSTABLE MP 92718

24211 9210 W

modifier les dispositifs de lumière

 Ø54	24213 0050 B iMAX II HONEYCOMB B	☐
 Ø54	24213 0060 iMAX II GLASS SBL	☐
 Ø54	24213 0070 iMAX II LINEAR SPREAD LENS	☐
 Ø54	24213 0090 iMAX II SOFTENING LENS	☐
 Ø54	24213 0100 iMAX II SPREAD LENS	☐

Terminez votre produit

 Ø78	24213 0010 B iMAX II TUBE ROUND B	☐
	24213 0010 FG iMAX II TUBE ROUND FG	☐
	24213 0010 MMAT iMAX II TUBE ROUND MMAT	☐
	24213 0010 W iMAX II TUBE ROUND W	☐
 Ø78	24213 0040 B iMAX II TUBE ROUND IP B	☐

DELTALIGHT

iMAX II ROUND ADJUSTABLE MP 92718

24211 9210 W

<u>24213 0040 FG</u>	iMAX II TUBE ROUND IP FG	☐
<u>24213 0040 MMAT</u>	iMAX II TUBE ROUND IP MMAT	☐
<u>24213 0040 W</u>	iMAX II TUBE ROUND IP W	☐

Notes: