



SPY 39 ON 2 93020 DIM8

24130 9328 BRG-B

AVAILABLE IN

BLACK-BLACK 24130 9328 B-B

BRUSHED ALU-BLACK 24130 9328 BRA-B

BRUSHED ANTHRACITE-BLACK 24130 9328 BRAT-B



BRUSHED COPPER-BLACK 24130 9328 BRCU-B

BRUSHED GOLD-BLACK 24130 9328 BRG-B

BRUSHED OLD BRONZE-BLACK 24130 9328 BROB-B

FULL WHITE 24130 9328 FW

WHITE-WHITE 24130 9328 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-20° INCL.DIMMABLE LED POWER SUPPLY 350/500mA-DC Current selection via jumper on power supply

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm)
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	2178lm // 17,2W // 127lm/W
LED TECHNICS (LUMINAIRE)	1776lm // 19,8W // 90lm/W

Requirements

SPY 39 TUBE or VISOR 39

For detailed installation instructions, please consult the manual : [24130_XXX8_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Light altering devices



24144 0030 B VISOR 39 B

☐

Finish your product



24144 0010 B SPY 39 TUBE B

☐

24144 0010 FBR SPY 39 TUBE FBR

☐

24144 0010 FG SPY 39 TUBE FG

☐

24144 0010 GC SPY 39 TUBE GC

☐

24144 0010 W SPY 39 TUBE W

☐

24144 0070 SPY 39 TUBE SBL

☐

Notes: