



## M52 - SPY 52 TW 96530 DIM5



### REFERENCE

24445 9045 W

### AVAILABLE IN

**BLACK** 24445 9045 B

**WHITE** 24445 9045 W



[View on website](#)



### General info

|                           |                                                                                                                |
|---------------------------|----------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                                         |
| <b>INSTALLATION</b>       | Low voltage systems Low voltage system mounted                                                                 |
| <b>INGRESS PROTECTION</b> | IP20                                                                                                           |
| <b>WEIGHT (KG)</b>        | 0.5                                                                                                            |
| <b>ADJUSTABILITY</b>      | 0° to 90° swiveling, 355° rotatable                                                                            |
| <b>INFORMATION</b>        | REFLECTOR FL-30°<br>EXCLLED POWER SUPPLY 48V-DC<br>DALI DT8 dimming<br>Optional REFLECTORS 20° & 45° available |

### Electrical info

|                     |               |
|---------------------|---------------|
| <b>ELECTRICAL</b>   | 48V-DC        |
| <b>CLASS</b>        | III           |
| <b>DIM TYPE</b>     | DALI          |
| <b>ENERGY CLASS</b> | E             |
| <b>CERTIFICATES</b> | CB, ENEC, EPD |

### Lightsource info

|                                    |                                                       |
|------------------------------------|-------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                   |
| <b>LIGHTSOURCE</b>                 | LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm |
| <b>TM-30 VALUES</b>                | Rf: 89 / Rg: 100                                      |
| <b>SDCM</b>                        | SDCM2                                                 |
| <b>RISKGROUP</b>                   | RG1                                                   |
| <b>LM80</b>                        | L90B10 > 50000                                        |
| <b>BEAMANGLE</b>                   | 30°                                                   |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1087lm // 9W // 121lm/W                               |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 694lm // 10,4W // 67lm/W                              |

### Remarks

Take a look at our **MAGNETIC PROFILES** movie

### Requirements







SPY 52 TUBE  
LED POWER SUPPLY 48V-DC

### Accessories

HONEYCOMB 42  
SPREAD LENS 42  
LINEAR SPREAD LENS 42  
SOFTENING LENS 42  
GLASS SBL 42

For detailed installation instructions, please consult the manual : [24445\\_XXX5\\_HAND.pdf](#)


FINISH YOUR SPECIFICATION

| LED power supplies                                                                                                                                                                                                                                                                                                                                                         |    | # of Fixtures             |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|---------------------------|
| <div><div></div><div># of fixtures indicates how many devices can be connected (min -&gt; max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div></div> |    | Min current   Max current |
| <div><div></div><div><div><b>300 89 48 100</b></div><div>LED POWER SUPPLY 48V-DC / 100W DIN</div><div>Dimtype: non-dimmable</div></div></div>                                                                                                                                              | 9  | <input type="text"/>      |
| <div><div></div><div><div><b>300 89 48 240</b></div><div>LED POWER SUPPLY 48V-DC / 240W DIN</div><div>Dimtype: non-dimmable</div></div></div>                                                                                                                                             | 23 | <input type="text"/>      |
| <div><div></div><div><div><b>21012 0230</b></div><div>LED POWER SUPPLY 48V-DC / 100W</div><div>Dimtype: non-dimmable</div><div>Cutout dimension (mm): 40</div></div></div>                                                                                                               | 9  | <input type="text"/>      |
| <div><div></div><div><div><b>21012 0240</b></div><div>LED POWER SUPPLY 48V-DC / 200W</div><div>Dimtype: non-dimmable</div><div>Cutout dimension (mm): 40</div></div></div>                                                                                                               | 19 | <input type="text"/>      |
| Light altering devices                                                                                                                                                                                                                                                                                                                                                     |    |                           |
| <div><div></div><div><div><b>19810 0010 B</b></div><div>HONEYCOMB 42 SINGLE USE B</div></div></div>                                                                                                                                                                                      |    | <input type="text"/>      |
| <div><div></div><div><div><b>19810 0020</b></div><div>LINEAR SPREAD LENS 42</div></div></div>                                                                                                                                                                                            |    | <input type="text"/>      |

# DELTALIGHT

## M52 - SPY 52 TW 96530 DIM5


24445 9045 W




**19810 0030** SPREAD LENS 42

☐

**19810 0040** SOFTENING LENS 42

☐


**19810 0050** GLASS SBL 42

☐

**19810 0060 B** HONEYCOMB 42 DOUBLE USE B

☐

### Finish your product



**19810 0100 B** SPY 52 TUBE B

☐

**19810 0100 FBR** SPY 52 TUBE FBR

☐

**19810 0100 FG** SPY 52 TUBE FG

☐


**19810 0100 GC** SPY 52 TUBE GC

☐

**19810 0100 W** SPY 52 TUBE W

☐

### Replaceable reflector / lens



**19810 0180** SPY 52 REFLECTOR 20°

☐

# DELTALIGHT

## M52 - SPY 52 TW 96530 DIM5

24445 9045 W



**19810 0190** SPY 52 REFLECTOR 45°




**19810 0240** SPY 52 REFLECTOR 30°




### COMPATIBLE COMPOSABLES

#### SPLITLINE M52 profile


#### Available Colours




**420 52 10 00** SPM52 - PROFILE 1m



**420 52 20 00** SPM52 - PROFILE 2m



**420 52 30 00** SPM52 - PROFILE 3m



**24413 0000** SPM52 - PROFILE



Notes: