HEDRA C



Hedra adds refinement, finesse and color to the range. Next to black and white, the Hedra is available in the Gold Colored anodization and Black Bronze finishes. These pendants play with light and design. The faceted design of the Hedra captures and reflects the ambient light with an ever-changing look as result. By combining decorative E26 bulbs with integrated LED, short with longer tubes, Black Bronze finish with Gold Colored, every set-up will be different and unique.

Specification	
LED Aperture	$1^{27}/_{32}$"
Installation Method:	4" junction box
Adjustability:	Fixed
Rating:	Damp

Performance	Hedra 39	Hedra 50
CRI / TM-30 (3000K):	90 / Rf: 90 / Rg: 99	90
SDCM:	1	2
LED Maintenance:	L90B10>50,000h	L90B10>50,000h
*Standard Power (SP):	7W	8W
*E26:		40W max - E26 Medium Base 120V

Delivered Lumens	2700K		3000K		3500K	
**Optic:	MD	WS	MD	WS	MD	WS
Hedra 39 SP:		507		547		549
Hedra 50 SP:	488		488		488	

Listing
ETL certified to US and Canadian safety standards.

Warranty
5-year limited warranty.

Ordering

SEE NEXT PAGE FOR HEDRA 45 C (SIZE 50)

Example: HDR3912-35WSSP-BBR-NA-PCPRINCD1-120

Luminaire	Size	Length	CCT	Optic**	Power*	Finish	Inner Finish	Type	Installation	Application	Controls***
HDR HEDRA	**39** 39mm / $1^{9}/_{16}$" Diameter (HEDRA 39 C)	**08** 800mm / $31^{1}/_{2}$" **12** 1200mm / $47^{1}/_{4}$"	**27** 2700K **30** 3000K **35** 3500K	**WS** Medium Wide Spot 45°	**SP** Standard Power	**B** Black **BBR** Black Bronze **GC** Gold Colored **W** White	**NA** No inner finish	**PC** Pendant, 5' cable suspended	**PR** Round coverplate for 4" junction box in Black for all Finishes (except White for White)	**INC** Integral Power Supply	**D1-120** 0-10V dim 120V

*** Contact factory for Dali, DMX, or other dimming options.

Related Products

Vizir/Hedra, Vizir/Hedra 2S, M-Vizir/Hedra, Superloop-Vizir/Hedra MDL

Ordering (cont.)

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER


Example: HDR5003-27MDSP-GC-B-PCPRINCD8-120

Luminaire	Size	Length	CCT	Optic**	Power*	Finish	Inner Finish	Type	Installation	Application	Controls***
HDR HEDRA	**50** 50mm / 2" Diameter (HEDRA 45 C)	**01** 150mm / $5^{15}/_{16}$"	**E** E26 medium base	**NA** Lamp not included	**20** Lamp not included, 20w max	**B** Black **BBR** Black Bronze **GC** Gold Colored **W** White	**NA** No inner finish	**PC** Pendant, 5' cable suspended	**PR** Round coverplate for 4" junction box in Black for all Finishes (except White for White)	**NA** 120V	**NA** Dimmability depends on lamp used
		02 195mm / $7^{11}/_{16}$" **03** 300mm / $11^{13}/_{16}$"	**27** 2700K **30** 3000K **35** 3500K	**WD** Medium Spot 40°	**SP** Standard Power	**B** Black **BBR** Black Bronze **GC** Gold Colored **W** White	**B** Black **FBR** Flemish Bronze **FG** Flemish Gold **MMAT** Gold Matte **SG** Silver Grey **W** White	**PC** Pendant, 5' cable suspended	**PR** Round coverplate for 4" junction box in Black for all Finishes (except White for White)	**INC** Integral Power Supply	**D8-120** FE ELV dim 120V
			E E26 medium base	**NA** Lamp not included	**20** Lamp not included, 20w max	**B** Black **BBR** Black Bronze **GC** Gold Colored **W** White	**NA** No inner finish	**PC** Pendant, 5' cable suspended	**PR** Round coverplate for 4" junction box in Black for all Finishes (except White for White)	**NA** 120V	**NA** Dimmability depends on lamp used

*** Contact factory for Dali, DMX, or other dimming options.

Finish Options

HEDRA 50 01 (E26)





BLACK


BLACK BRONZE


GOLD COLORED


WHITE

HEDRA 50 03 (E26)




BLACK


BLACK BRONZE



GOLD COLORED


WHITE

DELTALIGHT

Finish Options (cont.)

HEDRA 39 08




BLACK

BLACK BRONZE

GOLD COLORED

WHITE

HEDRA 39 12




BLACK

BLACK BRONZE

GOLD COLORED

WHITE

HEDRA 50 02





BLACK

BLACK BRONZE

GOLD COLORED

WHITE

HEDRA 50 03




BLACK


BLACK BRONZE


GOLD COLORED


WHITE

INNER FINISH - Only available with Size 50 Power SP


BLACK


FLEMISH BRONZE


FLEMISH GOLD



GOLD MATTE


SILVER GREY


WHITE


Photometric Data

HEDRA 39 STD POWER



WS 45°

HEDRA 50 STD POWER



MD 40°

Driver Options

D1

- Dimming Control 0-10V
- Dimming Range 10-100%
- Dim to off no
- Power Factor @ Full Load >0.97
- Efficiency @ Full Load ≥87

Dimmer Compatibility

- Leviton IP710-DLZ
- Lutron DVTV-XX

D8

- Dimming Control Phase Control
- Dimming Range 10-100%
- Dim to off no
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥80
- THD @ Full Load <5%

Dimmer Compatibility

- Leviton IPE04-1LZ
- Lutron DVELV-300P

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.