MILES



A collection of 4 purely handcrafted glass shapes, each in 4 different colours (pink, amber, smoke or mist), each recognizable yet unique in all respects. A family of suspensions that play on the visual contrast between the coloured and white blown glass, combined with different shapes and colours, also ideal for multiple compositions. All shapes and finishes are inspired by the interplay of opacity, translucency and transparency. Its translucent or milky forms and dynamic light offer a countless number of scenarios. When switched off its transparency makes MILES almost disappear. When switched on they provide a cozy and stylish luminous presence, stimulating senses and perceptions.

Specification	
Aperture:	$1^{5}/_{8}$"
Installation method:	4" junction box
Adjustability:	Fixed
Rating:	Damp

Performance	
CRI / TM-30 (2700K):	90 / Rf: 89 / Rg: 100
SDCM:	1
LED Maintenance:	L90B10>50,000h
*Standard Power (SP):	6.7W
[1]Remote Power Supply Capacity (# luminaires) SP:	D1-UNV min1-max2 D8-120 min1-max1
*E26:	20W max - E26 Medium Base 120V

Delivered Lumens	**2700K**			
Color:	**Amber**	**Mist**	**Pink**	**Smoke**
Miles C1:	565	560	566	524
Miles C2:	569	569	572	571
Miles C3:	556	565	541	405
Miles C4:	558	444	515	180

Listing
ETL certified to US and Canadian safety standards.

Warranty
5-year limited warranty.

Ordering
ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: MLSC3M-ENA20-B-PCPRBNANA

Luminaire	Glass Style	Glass Color	CCT	Optic	Power*	Finish	Type	Installation	Application	Controls***
MLS MILES	**C1** Wide cone glass **C2** Flat dome glass **C3** Small extended cone glass **C4** Wine bottle shaped glass	**A** Amber **M** Mist **P** Pink **S** Smoke	**27** 2700K	**WS** Medium Wide Spot 50°	**SP** Standard Power	**B** Black	**PC** Pendant, 5' cable suspended	**PRB** Round coverplate for 4" junction box in Black **PRW** Round coverplate for 4" junction box in White	**RMT** Remote Power Supply	**D1-UNV** 0-10V dim 120-277V **D1-347** 0-10V dim 347V **D8-120** FE ELV dim 120V
								NA Power Box includes black coverplate for 4" junction box	**PBB** Power Box Black	**D8-120** FE ELV dim 120V
			E E26 medium base	**NA** Lamp not included	**20** Lampl not included, 20w max	**B** Black	**PC** Pendant, 5' cable suspended	**PRB** Round coverplate for 4" junction box in Black	**NA** 120V	**NA** Dimmability depends on lamp used


1 Remote power supply capacity noted in table above.
*** Contact factory for Dali, DMX, or other dimming options.

Related Products

Soiree, Gibbo, Spy C, Hedra C

Finish Options

MILES C1





AMBER


MIST


PINK


SMOKE

MILES C2





AMBER


MIST


PINK


SMOKE

MILES C3





AMBER


MIST


PINK


SMOKE

MILES C4





AMBER


MIST


PINK


SMOKE

Accessories



MILES TUBE


BLACK
23944 0010 B


BLACK
INSTALLED
(Shown on C2 in PINK)



GOLD
23944 0010 M


GOLD
INSTALLED
(Shown on C1 in SMOKE)


DELTALIGHT

Photometric Data


MILES C1 STD POWER




WS 50° (Amber)



WS 50° (Mist)




WS 50° (Pink)




WS 50° (Smoke)


MILES C2 STD POWER




WS 50° (Amber)



WS 50° (Mist)




WS 50° (Pink)




WS 50° (Smoke)


MILES C3 STD POWER




WS 50° (Amber)



WS 50° (Mist)




WS 50° (Pink)




WS 50° (Smoke)


MILES C4 STD POWER




WS 50° (Amber)



WS 50° (Mist)



WS 50° (Pink)




WS 50° (Smoke)

Installation Options

REMOTE DRIVER (With Controls D8)

A: 8″ x **B:** 2″-1/2 x **C:** 2″-1/2
A: 203mm x **B:** 64mm x **C:** 64mm


- For Remote application
- ETL Listed
- Damp rated




REMOTE DRIVER (With Controls D1)

A: 8″ x **B:** 2″-3/16 x **C:** 4″-1/4
A: 203mm x **B:** 72mm x **C:** 108mm

- For Remote application
- ETL Listed
- Damp rated




PRB/PRW - COVERPLATE R 121



BLACK OR WHITE
Requires 4" junction box

PBB - POWER BOX



Requires 4" junction box



BLACK

Driver Options

D1

- Dimming Control 0-10V
- Dimming Range 1-100%
- Dim to off yes at 0.7mA
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥87
- THD @ Full Load <20%
- Title 24 Compliant

Dimmer Compatibility

- Leviton IP710-DLZ
- Lutron DVTV-XX
- WattStopper ADF-120277
- Synergy Lighting Controls ISD BC

D8

- Dimming Control Phase Control
- Dimming Range 10-100%
- Dim to off no
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥78
- THD @ Full Load <12%

Dimmer Compatibility

- Leviton IPE04-1LZ
- Lutron DVELV-300P

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.