
DELTALIGHT




OBIN ON 2 92736 DIM5

REFERENCE 30512 9235 W

AVAILABLE IN
BLACK 30512 9235 B
WHITE 30512 9235 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.4
ADJUSTABILITY	0° to 45° swiveling, 360° rotatable
INFORMATION	2 x LENS FL-36° INCL.DIMMABLE POWER SUPPLY

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 11,6W / CRI>90 (R9: 60) / 2700K / 1458lm)
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	36°
LED TECHNICS (LIGHT SOURCE)	2916lm // 23,2W // 125lm/W
LED TECHNICS (LUMINAIRE)	2515lm // 27W // 94lm/W

Requirements

SPY 90 TUBE

Accessories

HONEYCOMB 75

For detailed installation instructions, please consult the manual : **30512_XXX5_HAND.pdf**


DELTALIGHT

OBIN ON 2 92736 DIM5

30512 9235 W


FINISH YOUR SPECIFICATION

Light altering devices



19810 0110 B HONEYCOMB 75 SINGLE USE B ☐

Finish your product



19810 0170 B SPY 90 TUBE B ☐

19810 0170 CR SPY 90 TUBE CR ☐

19810 0170 DC SPY 90 TUBE DC ☐

19810 0170 FBR SPY 90 TUBE FBR ☐

19810 0170 FG SPY 90 TUBE FG ☐

19810 0170 GC SPY 90 TUBE GC ☐

19810 0170 PB SPY 90 TUBE PB ☐

19810 0170 W SPY 90 TUBE W ☐

Notes: