



COMPO L TW 94041

9 15738 9030 B



AVAILABLE IN

NEGRO 9 15738 9030 B

CHROMO 9 15738 9030 C

CHROMO OSCURO 9 15738 9030 DC

BLANCO 9 15738 9030 W



[View on website](#)



General info	
LOCATION	interior
INSTALLATION	Techo Empotrado
CUTOUT SHAPE/SIZE (MM)	redondo - 135
RECESSED DEPTH (MM)	130
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.466
ADJUSTABILITY	0° to 30° giratorio, 355° orientable

Electrical info	
CLASS	III
DIM TYPE	dependiendo del tipo de fuente de alimentación externa
ENERGY CLASS	G

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 17,8W / CRI>90 (R9: 50) / 1800K-4000K / 1832lm
RVALUES	rf: 89 / Rg: 100
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	1832lm // 17,8W // 101lm/W
LED TECHNICS (LUMINAIRE)	1257lm // 20,5W // 61lm/W

Requirements

LED POWER SUPPLY 500 mA - DC

Accessories

COMPO L HONEYCOMB SINGLE USE B

COMPO L LINEAR SPREAD LENS

COMPO L SPREAD LENS

COMPO L SOFTENING LENS

COMPO L GLASS SBL

For detailed installation instructions, please consult the manual : [9_15738_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required

FINISH YOUR SPECIFICATION

Fuente de alimentación LED	# of Fixtures
 web2print_power_supply_info_box	Min current Max current
15710 6000 LED POWER SUPPLY MULTIPOWER 20W DALI DT8 500mA	1

Mounting Kit	
 Cutout dimension (mm): 92	☐
15710 0030 B MOUNTING KIT COMPO L TRIM B	
15710 0030 W MOUNTING KIT COMPO L TRIM W	☐
 Cutout dimension (mm): 92	☐
15710 0060 MOUNTING KIT COMPO L TRIMLESS	

Dispositivos de modificación de Luz	
15710 2100 B COMPO L HONEYCOMB SINGLE USE B	☐
15710 2110 COMPO L LINEAR SPREAD LENS	☐
Cutout dimension (mm): 42	

DELTALIGHT

COMPO L TW 94041

9 15738 9030 B

<u>15710 2120</u>	COMPO L SPREAD LENS	☐
--------------------------	---------------------	--------------------------

Cutout dimension (mm): 42

<u>15710 2130</u>	COMPO L SOFTENING LENS	☐
--------------------------	------------------------	--------------------------

Cutout dimension (mm): 42

<u>15710 2140</u>	COMPO L GLASS SBL	☐
--------------------------	-------------------	--------------------------

Cutout dimension (mm): 42

Notes: