




## M26L - JUM-OH! 2R 93030 MDL

29411 9320 B

AVAILABLE IN  
**BLACK** 29411 9320 B



[View on website](#)



| General info                |                                                      |
|-----------------------------|------------------------------------------------------|
| LOCATION                    | indoor                                               |
| INSTALLATION                | Low voltage systems Low voltage system mounted       |
| INGRESS PROTECTION          | IP20                                                 |
| WEIGHT (KG)                 | 0.1                                                  |
| ADJUSTABILITY               | non adjustable                                       |
| INFORMATION                 | 2 x REFLECTOR FL-30°<br>EXCL.LED POWER SUPPLY 48V-DC |
| Electrical info             |                                                      |
| ELECTRICAL                  | 48V-DC                                               |
| CLASS                       | III                                                  |
| DIM TYPE                    | MDL = 1-10V or DALI or push button                   |
| ENERGY CLASS                | F                                                    |
| CERTIFICATES                | CB, ENEC                                             |
| Lightsource info            |                                                      |
| LIGHTSOURCE NAME            | LED                                                  |
| LIGHTSOURCE                 | LED cluster 4W / CRI>90 (R9: 60) / 3000K / 481lm     |
| TM-30 VALUES                | Rf: 92 / Rg: 99                                      |
| SDCM                        | SDCM3                                                |
| RISKGROUP                   | RG2                                                  |
| LM80                        | L80 > 150000                                         |
| BEAMANGLE                   | 30°                                                  |
| LED TECHNICS (LIGHT SOURCE) | 481lm // 4W // 120lm/W                               |
| LED TECHNICS (LUMINAIRE)    | 398lm // 4,6W // 86lm/W                              |
| Requirements                |                                                      |
| LED POWER SUPPLY 48V-DC     |                                                      |
| Options                     |                                                      |
| DIMMABLE MODULATOR          |                                                      |

For detailed installation instructions, please consult the manual : [29411\\_XXX0\\_HAND.pdf](#)

M26L - JUM-OH! 2R 93030 MDL

29411 9320 B


FINISH YOUR SPECIFICATION

Current supply

# of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**21032 0030** SMART 48 MODULATOR PLUG-IN WD

Dimtype: WDL = wireless dimmable


41

SMART 48

# of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 90 011** SMART 48 MODULATOR DIM9

Dimtype: 1-10V or DALI or push button

41



**300 90 012** SMART 48 MODULATOR WD

Dimtype: WDL = wireless dimmable


41

LED power supplies

# of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

Dimtype: non-dimmable

21



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

Dimtype: non-dimmable

52







# DELTALIGHT

## M26L - JUM-OH! 2R 93030 MDL

29411 9320 B

|                                                                                  |                                                  |    |                          |
|----------------------------------------------------------------------------------|--------------------------------------------------|----|--------------------------|
|  | <b>21012 0230</b> LED POWER SUPPLY 48V-DC / 100W | 21 | <input type="checkbox"/> |
|                                                                                  | Dimtype: non-dimmable                            |    |                          |
|                                                                                  | Cutout dimension (mm): 40                        |    |                          |
|  | <b>21012 0240</b> LED POWER SUPPLY 48V-DC / 200W | 43 | <input type="checkbox"/> |
|                                                                                  | Dimtype: non-dimmable                            |    |                          |
|                                                                                  | Cutout dimension (mm): 40                        |    |                          |


### COMPATIBLE COMPOSABLES

| SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)                                    | Available Colours                                                                     |
|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|    |    |
|  |  |
|  |  |
|  |  |
| SHIFTLINE M35R profile                                                              | Available Colours                                                                     |
|  |  |
|  |  |


# DELTALIGHT

## M26L - JUM-OH! 2R 93030 MDL

29411 9320 B



**23375 0020** SLM35R - PROFILE 2m



**23375 0030** SLM35R - PROFILE 3m



Notes: