
DELTALIGHT




M20/M26H - OCTAV 39 93040 DIM5

REFERENCE 29022 9335 W

AVAILABLE IN
BLACK 29022 9335 B
FLEMISH BRONZE 29022 9335 FBR
FLEMISH GOLD 29022 9335 FG
GOLD COLOURED 29022 9335 GC
WHITE 29022 9335 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-40° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	737lm // 9,9W // 75lm/W

Remarks

Take a look at our MAGNETIC PROFILES movie

Requirements

SPY 39 L TUBE
LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : **29022_XXX5_HAND.pdf**

M20/M26H - OCTAV 39 93040 DIM5

29022 9335 W


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 10

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 24


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 10

Dimtype: non-dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W — 20

Dimtype: non-dimmable

Cutout dimension (mm): 40

Finish your product



24144 0020 B SPY 39 L TUBE B

24144 0020 FBR SPY 39 L TUBE FBR

24144 0020 FG SPY 39 L TUBE FG





24144 0020 GC SPY 39 L TUBE GC




24144 0020 W SPY 39 L TUBE W

M20/M26H - OCTAV 39 93040 DIM5

29022 9335 W

COMPATIBLE COMPOSABLES


SHIFTLINE M26H + SBL		Available Colours
	**30411 9205** SHIFTLINE M26H + SBL 2m DIM5	
	**30411 9305** SHIFTLINE M26H + SBL 2m DIM5	
	**30412 9205** SHIFTLINE M26H + SBL 3m DIM5	
	**30412 9305** SHIFTLINE M26H + SBL 3m DIM5	
	**30413 9205** SHIFTLINE M26H + SBL 4m DIM5	
	**30413 9305** SHIFTLINE M26H + SBL 4m DIM5	

SHIFTLINE M26H profile		Available Colours
	**23359 0000** SLM26H - PROFILE	
	**23359 0010** SLM26H - PROFILE 1m	
	**23359 0020** SLM26H - PROFILE 2m	

DELTALIGHT

M20/M26H - OCTAV 39 93040 DIM5

29022 9335 W



23359 0030 SLM26H - PROFILE 3m

SPLITLINE M20 ST profile — Available Colours



23397 0000 SPM20 ST - PROFILE




23397 0020 SPM20 ST - PROFILE 2m




23397 0030 SPM20 ST - PROFILE 3m


SPLITLINE M20 profile — Available Colours




420 20 10 00 SPM20 - PROFILE 1m



420 20 20 00 SPM20 - PROFILE 2m



420 20 30 00 SPM20 - PROFILE 3m



23301 0000 SPM20 - PROFILE B

Notes: