



## M20/M26H - OCTAV 39 93040 DIM5

29022 9335 W

AVAILABLE IN



**BLACK** 29022 9335 B

**FLEMISH BRONZE** 29022 9335 FBR

**FLEMISH GOLD** 29022 9335 FG

**GOLD COLOURED** 29022 9335 GC

**WHITE** 29022 9335 W



[View on website](#)



### General info

|                           |                                                  |
|---------------------------|--------------------------------------------------|
| <b>LOCATION</b>           | indoor                                           |
| <b>INSTALLATION</b>       | Low voltage systems Low voltage system mounted   |
| <b>INGRESS PROTECTION</b> | IP20                                             |
| <b>WEIGHT (KG)</b>        | 0.4                                              |
| <b>ADJUSTABILITY</b>      | 0° to 85° swiveling, 355° rotatable              |
| <b>INFORMATION</b>        | REFLECTOR WFL-40°<br>EXCLLED POWER SUPPLY 48V-DC |

### Electrical info

|                     |          |
|---------------------|----------|
| <b>ELECTRICAL</b>   | 48V-DC   |
| <b>CLASS</b>        | III      |
| <b>DIM TYPE</b>     | DALI     |
| <b>ENERGY CLASS</b> | E        |
| <b>CERTIFICATES</b> | CB, ENEC |

### Lightsource info

|                                    |                                                   |
|------------------------------------|---------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                               |
| <b>LIGHTSOURCE</b>                 | LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm |
| <b>TM-30 VALUES</b>                | rf: 90 / Rg: 99                                   |
| <b>SDCM</b>                        | SDCM1                                             |
| <b>RISKGROUP</b>                   | RG1                                               |
| <b>LM80</b>                        | L90B10 > 50000                                    |
| <b>BEAMANGLE</b>                   | 40°                                               |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1089lm // 8,6W // 127lm/W                         |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 737lm // 9,9W // 75lm/W                           |

### Remarks

[Take a look at our MAGNETIC PROFILES movie](#)

### Requirements

SPY 39 L TUBE

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [29022\\_XXX5\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION


#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

10

Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: non-dimmable



**21012 0230** LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: non-dimmable

Cutout dimension (mm): 40




**21012 0240** LED POWER SUPPLY 48V-DC / 200W

20

Dimtype: non-dimmable

Cutout dimension (mm): 40

#### Finish your product



**24144 0020 B** SPY 39 L TUBE B

**24144 0020 FBR** SPY 39 L TUBE FBR

**24144 0020 FG** SPY 39 L TUBE FG

**24144 0020 GC** SPY 39 L TUBE GC



**24144 0020 W** SPY 39 L TUBE W




# DELTALIGHT

## M20/M26H - OCTAV 39 93040 DIM5

29022 9335 W

### COMPATIBLE COMPOSABLES

| SHIFTLINE M26H + SBL                                                               |                                                | Available Colours                                                                     |
|------------------------------------------------------------------------------------|------------------------------------------------|---------------------------------------------------------------------------------------|
|   | <b>30411 9205</b> SHIFTLINE M26H + SBL 2m DIM5 |    |
|   | <b>30411 9305</b> SHIFTLINE M26H + SBL 2m DIM5 |    |
|   | <b>30412 9205</b> SHIFTLINE M26H + SBL 3m DIM5 |    |
|  | <b>30412 9305</b> SHIFTLINE M26H + SBL 3m DIM5 |  |
|  | <b>30413 9205</b> SHIFTLINE M26H + SBL 4m DIM5 |  |
|  | <b>30413 9305</b> SHIFTLINE M26H + SBL 4m DIM5 |  |

| SHIFTLINE M26H profile                                                              |                                       | Available Colours                                                                     |
|-------------------------------------------------------------------------------------|---------------------------------------|---------------------------------------------------------------------------------------|
|  | <b>23359 0000</b> SLM26H - PROFILE    |  |
|  | <b>23359 0010</b> SLM26H - PROFILE 1m |  |
|  | <b>23359 0020</b> SLM26H - PROFILE 2m |  |

# DELTALIGHT

## M20/M26H - OCTAV 39 93040 DIM5

29022 9335 W



**23359 0030** SLM26H - PROFILE 3m



### SPLITLINE M20 ST profile

Available Colours



**23397 0000** SPM20 ST - PROFILE



**23397 0020** SPM20 ST - PROFILE 2m




**23397 0030** SPM20 ST - PROFILE 3m




### SPLITLINE M20 profile


Available Colours




**420 20 10 00** SPM20 - PROFILE 1m



**420 20 20 00** SPM20 - PROFILE 2m



**420 20 30 00** SPM20 - PROFILE 3m



**23301 0000** SPM20 - PROFILE B



Notes: