
DELTALIGHT




FRAX S 930 LINEAR V

REFERENCE 26001 9330 N

AVAILABLE IN
ALU GREY 26001 9330 A
FLEMISH BRONZE OUTDOOR 26001 9330 FBRX
ANTHRACITE 26001 9330 N





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted,Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	1.5
ADJUSTABILITY	0° to 120° swiveling, 360° rotatable
INFORMATION	4 x LENS SP-14° INCL.LED POWER SUPPLY 700mA-DC INCL.LINEAR SPREAD LENS VERTICAL Oval spread 60°-15°

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 8W / CRI>90 (R9: 60) / 3000K / 961lm
TM-30 VALUES	Rf: 92 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	14°
LED TECHNICS (LIGHT SOURCE)	961lm // 8W // 120lm/W
LED TECHNICS (LUMINAIRE)	673lm // 9W // 73lm/W

Options

FRAX ANTI VANDAL SCREWS

Accessories

FRAX S KAP

DELTALIGHT


FRAX S 930 LINEAR V

26001 9330 N

For detailed installation instructions, please consult the manual : **26001_XX30_HAND.pdf**


FINISH YOUR SPECIFICATION

Light altering devices



26070 0010 N FRAX S KAP N ☐

Other



26070 0030 FRAX ANTI VANDAL SCREWS 5 PCS ☐

Notes: