



## M26L - SPY 39 WALLWASH 930 MDL

23433 9300 BROB

AVAILABLE IN

- BLACK** 23433 9300 B
- BRUSHED ALU** 23433 9300 BRA
- BRUSHED ANTHRACITE** 23433 9300 BRAT
- BRUSHED COPPER** 23433 9300 BRCU
- BRUSHED GOLD** 23433 9300 BRG
- BRUSHED OLD BRONZE** 23433 9300 BROB
- FLEMISH BRONZE** 23433 9300 FBR
- FLEMISH GOLD** 23433 9300 FG
- GOLD COLOURED** 23433 9300 GC
- WHITE** 23433 9300 W



 [View on website](#)



### General info

|                           |  |
|---------------------------|--|
| <b>LOCATION</b>           | indoor   |
| <b>INSTALLATION</b>       | Low voltage systems Low voltage system mounted |
| <b>INGRESS PROTECTION</b> | IP20   |
| <b>WEIGHT (KG)</b>        | 0.3  |
| <b>ADJUSTABILITY</b>      | 0° to 85° swiveling, 360° rotatable            |
| <b>INFORMATION</b>        | WALLWASH LENS<br>EXCL.LED POWER SUPPLY 48V-DC  |

### Electrical info

|                     |                                    |
|---------------------|------------------------------------|
| <b>ELECTRICAL</b>   | 48V-DC                             |
| <b>CLASS</b>        | III                                |
| <b>DIM TYPE</b>     | MDL = 1-10V or DALI or push button |
| <b>ENERGY CLASS</b> | E                                  |

### Lightsource info

|                                    |  |
|------------------------------------|--|
| <b>LIGHTSOURCE NAME</b>            | LED  |
| <b>LIGHTSOURCE</b>                 | LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm |
| <b>TM-30 VALUES</b>                | rf: 90 / Rg: 99                                  |
| <b>SDCM</b>                        | SDCM1  |
| <b>RISKGROUP</b>                   | RG1  |
| <b>LM80</b>                        | L90B10 > 50000                                   |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 787lm // 5,8W // 135lm/W                         |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 431lm // 6,7W // 65lm/W                          |

### Requirements

LED POWER SUPPLY 48V-DC

### Options

DIMMABLE MODULATOR

# DELTALIGHT

## M26L - SPY 39 WALLWASH 930 MDL


23433 9300 BROB

For detailed installation instructions, please consult the manual : [23433\\_XXX0\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### Current supply

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**21032 0030** SMART 48 MODULATOR PLUG-IN WD

19

Dimtype: WDL = wireless dimmable

#### SMART 48

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 90 011** SMART 48 MODULATOR DIM9

19

Dimtype: 1-10V or DALI or push button




**300 90 012** SMART 48 MODULATOR WD

19

Dimtype: WDL = wireless dimmable

#### LED power supplies

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

10

Dimtype: non-dimmable

# DELTALIGHT

## M26L - SPY 39 WALLWASH 930 MDL

23433 9300 BROB



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: non-dimmable




**21012 0230** LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: non-dimmable

Cutout dimension (mm): 40



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

20

Dimtype: non-dimmable

Cutout dimension (mm): 40

## COMPATIBLE COMPOSABLES

### SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)

### Available Colours



**23358 0000** SLM26L - PROFILE



**23358 0010** SLM26L - PROFILE 1m



**23358 0020** SLM26L - PROFILE 2m



**23358 0030** SLM26L - PROFILE 3m



Notes: