





M26L - HALOSCAN MP 92714 DIM5

23124 9215 B

AVAILABLE IN
BLACK 23124 9215 B
WHITE 23124 9215 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 45° swiveling, 355° rotatable
INFORMATION	LENS SP-14° EXCL.LED POWER SUPPLY 48V-DC
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	14°
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	889lm // 9,9W // 90lm/W

Remarks

Take a look at our MAGNETIC PROFILES movie

Requirements

LED POWER SUPPLY 48V-DC

Accessories





HALOSCAN HONEYCOMB
 HALOSCAN LINEAR SPREAD LENS
 HALOSCAN KAP MP

M26L - HALOSCAN MP 92714 DIM5

23124 9215 B

For detailed installation instructions, please consult the manual : [23124_XXX5_HAND.pdf](#)


FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures	
		Min current Max current	
 55 100 90 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable			10
 63 114 125 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable			24
 17 298 30 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40			10
 22 392 30 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40			20
Light altering devices			
 072 23110 0040 HALOSCAN LINEAR SPREAD LENS			
 072 23110 0050 B HALOSCAN HONEYCOMB B			

DELTALIGHT

M26L - HALOSCAN MP 92714 DIM5

23124 9215 B



23110 0060 B HALOSCAN KAP MP B




23110 0060 W HALOSCAN KAP MP W




COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


Available Colours




23358 0000 SLM26L - PROFILE



23358 0010 SLM26L - PROFILE 1m



23358 0020 SLM26L - PROFILE 2m




23358 0030 SLM26L - PROFILE 3m




SHIFTLINE M35R profile


Available Colours



23375 0000 SLM35R - PROFILE



23375 0010 SLM35R - PROFILE 1m




23375 0020 SLM35R - PROFILE 2m



DELTALIGHT

M26L - HALOSCAN MP 92714 DIM5

23124 9215 B



23375 0030 SLM35R - PROFILE 3m



Notes: