
DELTALIGHT




NEEDLE 1 TRC OK 93013

REFERENCE 25015 9310 BBR

AVAILABLE IN
BLACK BRONZE 25015 9310 BBR
FLEMISH GOLD 25015 9310 FG





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	0° to 50° swiveling, 350° rotatable
INFORMATION	LENS SP-13° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 3,9-5,7W / CRI>90 (R9: 55) / 3000K / 385-519lm
TM-30 VALUES	Rf: 92 / Rg: 98
SDCM	SDCM2
RISKGROUP	RG2 (threshold 0,6m)
LM80	L90B10 > 41000
BEAMANGLE	13°
LED TECHNICS (LIGHT SOURCE)	519lm // 5,7W // 90lm/W
LED TECHNICS (LUMINAIRE)	364lm // 6,6W // 56lm/W

Requirements

CONNECTION TRIMLESS
LED POWER SUPPLY 350 / 500mA-DC DIM

For detailed installation instructions, please consult the manual : **25015_XXXX_HAND.pdf**

DELTALIGHT

NEEDLE 1 TRC OK 93013

25015 9310 BBR


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 — 3 ☐

Dimtype: 1-10V


Cutout dimension (mm): 30



300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 — 3 ☐

Dimtype: DALI


Cutout dimension (mm): 45



300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL — 3 ☐

Dimtype: non-dimmable


Cutout dimension (mm): 30



300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL — 3 ☐

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 45



300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1 — 3 ☐

Dimtype: 1-10V


Cutout dimension (mm): 30



300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 — 3 ☐

Dimtype: DALI


Cutout dimension (mm): 45



300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL — 3 ☐

Dimtype: non-dimmable

Cutout dimension (mm): 30




300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL — 3 ☐

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45

NEEDLE 1 TRC OK 93013


25015 9310 BBR



300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 — 3 | 3

Dimtype: mains (phase cut-off) or push button


Cutout dimension (mm): 56



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 — 6(6) | 6(6)

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 82



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 — 2->4(3) | 4(2)


Dimtype: 1-10V or push button

Cutout dimension (mm): 72



300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 — 3


Dimtype: 1-10V or DALI or push button



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 — 4(3) | 4(2)

Dimtype: DALI


Cutout dimension (mm): 72



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 — 2->9(10) | 9(6)

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 84



300 90 92 LED POWER SUPPLY 500mA-DC / 21W — 3(1)

Dimtype: non-dimmable


Cutout dimension (mm): 48



300 90 108 LED POWER SUPPLY 350mA-DC / 8W — 1

Dimtype: non-dimmable


Cutout dimension (mm): 40



300 90 116 LED POWER SUPPLY 350mA-DC / 18W DIM8 — 3->4

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 55



300 90 119 LED POWER SUPPLY 500mA-DC / 11W DIM8 — 1


Dimtype: mains (phase cut-off)

Cutout dimension (mm): 42

DELTALIGHT

NEEDLE 1 TRC OK 93013

25015 9310 BBR



300 90 121 LED POWER SUPPLY 500mA-DC / 20W DIM8 2->3

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 55



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 2->4(3) | 3(2)

Dimtype: 1-10V or push button


Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 4(3) | 3(2)

Dimtype: DALI


Cutout dimension (mm): 55



300 90 134 LED POWER SUPPLY MULTI-POWER HV DIM7 2->8(8) | 8(6) | -

Dimtype: 1-10V or push button


Cutout dimension (mm): 84



300 90 135 LED POWER SUPPLY MULTI-POWER HV 5->7 | 4->7 | 4->6

Dimtype: non-dimmable


Cutout dimension (mm): 90



300 90 3112 LED POWER SUPPLY 350mA-DC / 16W DIM8 2->3

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 43



300 90 5120 LED POWER SUPPLY 500mA-DC / 22W DIM8 3->3

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 61



21012 0010 LED POWER SUPPLY MULTI POWER 2->3 | 3

Dimtype: non-dimmable


Cutout dimension (mm): 50



21012 0021 LED POWER SUPPLY MULTI POWER DIM1 4 | 4

Dimtype: 1-10V

Cutout dimension (mm): 54



21012 0035 LED POWER SUPPLY MULTI POWER DIM5 4 | 4


Dimtype: DALI

Cutout dimension (mm): 54

DELTALIGHT

NEEDLE 1 TRC OK 93013


25015 9310 BBR



21012 004W LED POWER SUPPLY MULTI-POWER WDL 6(6) | 5(5)

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 84



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL 4 | 4 | 4

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 54



21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 2->2

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 50



21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 3->3

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 50



21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 2->2

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 55



21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 4->4

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 55



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 3 | 3 | 3

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 48



21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 4(3)

Dimtype: non-dimmable


Cutout dimension (mm): 60



21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 4(2)

Dimtype: non-dimmable

Cutout dimension (mm): 60



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 3


Dimtype: DALI

Cutout dimension (mm): 30

DELTALIGHT

NEEDLE 1 TRC OK 93013

25015 9310 BBR




21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 3

Dimtype: DALI

Cutout dimension (mm): 30

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)

Notes: