

COMPO S 92720

9 15711 9220 B


AVAILABLE IN

BLACK 9 15711 9220 B



CHROMED 9 15711 9220 C

DARK CHROMED 9 15711 9220 DC

WHITE 9 15711 9220 W



EXCLUSIVELY AVAILABLE IN INDIA



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 90
RECESSED DEPTH (MM)	85
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.124
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6,4W / CRI>90 / 2700K / 476lm
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	476lm // 6,4W // 115lm/W
LED TECHNICS (LUMINAIRE)	377lm // 7,4W // 51lm/W

Requirements

LED POWER SUPPLY 350 mA - DC

Accessories

COMPO S HONEYCOMB SINGLE USE B

COMPO S LINEAR SPREAD LENS

COMPO S SPREAD LENS

COMPO S SOFTENING LENS

COMPO S GLASS SBL

For detailed installation instructions, please consult the manual : [9_15711_XXX0_HAND.pdf](#)

COMPO S 92720

9 15711 9220 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	System ceiling	15710 0010 - MOUNTING KIT COMPO S TRIM Required
		15710 0040 - MOUNTING KIT COMPO S TRIMLESS Required
	Plasterboard	15710 0010 - MOUNTING KIT COMPO S TRIM Required
		15710 0040 - MOUNTING KIT COMPO S TRIMLESS Required
	Wood	15710 0010 - MOUNTING KIT COMPO S TRIM Required
		15710 0040 - MOUNTING KIT COMPO S TRIMLESS Required

FINISH YOUR SPECIFICATION

LED Power supply		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
15710 3100	LED POWER SUPPLY 18W NO DIM 1400mA	1->4
15710 3300	LED POWER SUPPLY MULTIPOWER 15W NO DIM 350mA	1->2
15710 3800	LED POWER SUPPLY MULTIPOWER 10W DIM8 350mA	1
15710 4500	LED POWER SUPPLY MULTIPOWER 12W DIM1 350mA	1
15710 5000	LED POWER SUPPLY MULTIPOWER 55W DALI DT6 1400mA	1->13
Dimtype: DALI		
15710 5300	LED POWER SUPPLY MULTIPOWER 12W DALI DT6 350mA	1
Dimtype: DALI		

Mounting kits		
	15710 0010 B MOUNTING KIT COMPO S TRIM B	
Cutout dimension (mm): 55		
	15710 0010 W MOUNTING KIT COMPO S TRIM W	

DELTALIGHT

COMPO S 92720

9 15711 9220 B



15710 0040 MOUNTING KIT COMPO S TRIMLESS

☐

Cutout dimension (mm): 55

Light altering devices

15710 0100 B COMPO S HONEYCOMB SINGLE USE B

☐

15710 0110 COMPO S LINEAR SPREAD LENS

☐

Cutout dimension (mm): 26,5

15710 0120 COMPO S SPREAD LENS

☐

Cutout dimension (mm): 26,5

15710 0130 COMPO S SOFTENING LENS

☐

Cutout dimension (mm): 26,5

15710 0140 COMPO S GLASS SBL

☐

Cutout dimension (mm): 26,5

Notes: