





D-LINER 19 INF LOC1 1390 94058 RD

32019 9420 B

AVAILABLE IN
BLACK 32019 9420 B



 [View on website](#)



| General info | |
|---------------------------|---|
| LOCATION | indoor |
| INSTALLATION | Ceiling Recessed |
| INGRESS PROTECTION | IP20 |
| WEIGHT (KG) | 0 |
| ADJUSTABILITY | non adjustable |
| INFORMATION | 60 x REFLECTOR 58° EXCL.LED POWER SUPPLY 650mA-DC INCL.1 x CABLE 2 x 0,75mm ² - 0,5m + WIELAND PLUG GST08i2 male green |

| Electrical info | |
|---------------------|-----|
| CLASS | III |
| ENERGY CLASS | C |


| Lightsource info | |
|------------------------------------|---|
| LIGHTSOURCE NAME | LED |
| LIGHTSOURCE | LED cluster 21,6W / CRI>90 / 4000K / 3942lm |
| BEAMANGLE | 58° |
| LED TECHNICS (LIGHT SOURCE) | 3942lm // 21,6W // 183lm/W |
| LED TECHNICS (LUMINAIRE) | 3355lm // 24,8W // 135lm/W |

| Requirements | |
|-----------------------------------|--|
| LED POWER SUPPLY SET LOC PARALLEL | |

| Options | |
|-------------------------------|--|
| CONNECTING CABLE LOC PARALLEL | |

For detailed installation instructions, please consult the manual : [32019_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

| Ceiling Type | Mounting Kit |
|---|--------------|
|  Acoustic climate-control ceiling Interalu SAPP | - |

DELTALIGHT

D-LINER 19 INF LOC1 1390 94058 RD

32019 9420 B



Acoustic climate-control ceiling Hunter Douglas 30BD

FINISH YOUR SPECIFICATION


Emergency units

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



32010 0195 EMERGENCY UNIT 1h LOC PARALLEL DIM5

1

Dimtype: DALI

Current supply



32010 1200 T CONNECTOR LOC PARALLEL



32010 1310 CONNECTING CABLE LOC PARALLEL 1m



32010 1320 CONNECTING CABLE LOC PARALLEL 2m



32010 1330 CONNECTING CABLE LOC PARALLEL 3m



32010 1340 CONNECTING CABLE LOC PARALLEL 4m

DELTALIGHT

D-LINER 19 INF LOC1 1390 94058 RD

32019 9420 B



32010 1350 CONNECTING CABLE LOC PARALLEL 5m


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



32010 0115 LED POWER SUPPLY SET LOC PARALLEL 650mA / 35W DIM5

1


Dimtype: DALI



32010 0165 LED POWER SUPPLY SET LOC PARALLEL 1300mA / 100W DIM5

2->2

Dimtype: DALI



32010 0455 LED POWER SUPPLY SET LOC PARALLEL 2080mA / 100W DIM5

3->3

Dimtype: DALI

Notes: