





SL19 - SPY 39 L 93040 MDL
27032 9330 W

AVAILABLE IN
BLACK 27032 9330 B
FLEMISH BRONZE 27032 9330 FBR
FLEMISH GOLD 27032 9330 FG
GOLD COLOURED 27032 9330 GC
WHITE 27032 9330 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-40° EXCLLED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	D
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	737lm // 9,9W // 75lm/W

Requirements	
SPY 39 L TUBE	
LED POWER SUPPLY 48V-DC	

Options	
DIMMABLE MODULATOR	

For detailed installation instructions, please consult the manual : [27032_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

SMART 48

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

19

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

19

Dimtype: WDL = wireless dimmable

LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

10

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W

20

Dimtype: non-dimmable

Cutout dimension (mm): 40

DELTALIGHT



SL19 - SPY 39 L 93040 MDL

27032 9330 W

Finish your product

	<u>24144 0020 B</u> SPY 39 L TUBE B	☐
	<u>24144 0020 FBR</u> SPY 39 L TUBE FBR	☐
	<u>24144 0020 FG</u> SPY 39 L TUBE FG	☐
	<u>24144 0020 GC</u> SPY 39 L TUBE GC	☐
	<u>24144 0020 W</u> SPY 39 L TUBE W	☐

COMPATIBLE COMPOSABLES

SHIFTLINE 19 profile	Available Colours
	☒ ☐
<u>27011 0050</u> SL19 - PROFILE 2m	
	☒ ☐
<u>27011 0060</u> SL19 - PROFILE 3m	

Notes: